

## Specification Sheet

Part Number: LTM250C2



Lashing Tie Mount, .73" x 1.5", .25" Screw, PA66HS, Black, 100/pkg

**Article Number** 151-00358

**Type** LTM250

**Color** Black (BK)

**Features & Benefits**

- The strap is parallel to the mount when inserted into the head, providing a fixed insertion point for the cable tie.

**Quantity Per** bag

**Product Description**

The lashing tie mount is designed to snap into the T250 lashing tie. The tie head is assembled perpendicular to the mount. The strap is parallel to the mount when inserted into the head. The lashing tie mount is recommended for indoor or outdoor wall mount cable applications.

**Short Description** Lashing Tie Mount, .73" x 1.5", .25" Screw, PA66HS, Black, 100/pkg

**Global Part Name** LTM250-PA66HS-BK

**Length L (Imperial)** 1.5

**Length L (Metric)** 37.1

**Fixation Method** Screw Mounting and Rivet

**Width W (Imperial)** 0.73

**Width W (Metric)** 18.5

**Cable Ties** T250

**Height H (Imperial)** 0.38

**Height H (Metric)** 9.6

**Cable Tie Width Max (Imperial)** 0.49

**Cable Tie Width Max (Metric)** 12.5

**Mounting Hole Diameter D (Imperial)** 0.26

**Mounting Hole Diameter D (Metric)** 6.6 mm

**Mounting Hole Diameter D Max (Metric)** 6.6

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +257°F (-40°C to +125°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.