

WOD-50DDXC

50.23" H 29.5" W x 42" D (26 RU) Outdoor Enclosure



General

*Approximate Weight

- 192 Lbs. assembled
- 262 Lbs. shipping weight

Doors

- Two - Secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .375" aluminum filled gaskets
- EMKA Wind Lock on Each Door

Material

- .125" Alumiflex®
- Finish: Painted cream
- RF properties: Non-ferrous

Vents

- 30 louvers per door
- 16 top louvers – In top cover, under Alumishield®
- One removable filter panel per door
- 16 fixed filter pads in top cover

Handles

- Zinc Die Powder-coated Black EMKA Three Point Padlocking Handles

Exterior Screws

- Stainless steel with sealing washers & nylon locking nuts

Racking Specifications

Rails

- 2 Sets of 19" or 23" Reversible Racking Rails w/RU Markings and Pass-through Holes
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex®)

Rail Pass-Throughs

- Each rail has 2 pass-through holes with grommets. Holes are 1.75" diameter

Positioning

- All rails fully adjustable from front to rear

Inside Clearance - Less Rails

- Height: 49.98"
- Width: 27.625"
- Depth: 35.75"

Ratings

NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c) , NEMA 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

- Height: 46"
- Width: 23.5"

Exterior Cabinet Dimensions

Main Body

- Height: 50.23"
- Width: 29.5"
- Depth: 42"

Alumishield®

- Hang down height: 1.71"
- Width: 32.46"
- Depth: 44.67"

Handles

- Protrude 2.2"

Total Space Occupied

- Height: 50.855"
- Width: 32.46"
- Depth: 46.4"



Pictures shown are examples only.
See details for specifications.