

DFJ-2S123-3M

HELIAX® FiberFeed® Discrete, 2 single mode fiber, 5 mm armored LSZH cable. End 1: DLC. End 2: DLC, 3 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Wireless Fiber Cable Assemblies
Product Brand	FiberFeed® HELIAX®
Product Series	DFJ
Ordering Note	CommScope® non-standard product

General Specifications

Construction Type	Discrete fiber tail
Interface, Connector A	DLC
Interface, Connector B	DLC
Jacket Color	Black
Total Fibers, quantity	2

Dimensions

Cord Length	3 m 9.843 ft
Diameter Over Jacket	4.8 mm 0.189 in

Optical Specifications

Fiber Type	G.657.B3
Assembly Insertion Loss, typical	0.5 dB
Assembly Insertion Loss, typical note	Insertion loss is measured at 1310 and 1550 nm

Environmental Specifications

DFJ-2S123-3M

Operating Temperature -40 °C to +75 °C (-40 °F to +167 °F)

Environmental Space Low Smoke Zero Halogen (LSZH)

Packaging and Weights

Cable weight 25 kg/km | 16.799 lb/kft

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



* Footnotes

Assembly Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)