



Patent No. US 9,520,640

## EM-M20007 LTE-Poly Pro IP66 Rated Flexible Poly-Band Antenna 4G/LTE NMO Applications

- Capacitive Coupled Design Optimizes LTE Signal Performance while Maintaining Low-Profile Tapered Form Factor
- Flexible Elastomeric Polymer Housing Resists High Speed Impact and Damage from low hanging obstructions
- Dust and O-ring Seals for Reliable High Pressure Car Wash & Waterproof Performance (IP66)
- Next Gen Design Incorporates Expanded Frequency Range and Reduced Height
- *Patented* Multi-band Performance to Comply Simultaneously with all LTE Operational Bands

### Electrical Specifications

Frequency Bands	698-960 MHz / 1710-2700 MHz
VSWR	1.5:1 typical, 2:1 max
Impedance	50Ω
Gain	698-960 MHz
	2 dBi (698-960 MHz)
	1710-2150 MHz
	3 dBi (1710-2150 MHz)
	2150-2700 MHz
	5 dBi (2150-2700 MHz)
Power Rating	100 W
Polarization	Linear, Vertical
E-Plane	70 Degrees / 35 Degrees, Nominal
H-Plane	Omnidirectional
Ground Plane	Required

### Mechanical Specifications

Height	3.63 in. (92 mm)
Diameter	1.6 in. (40 mm)
NMO Mount Type*	EM-M11001-195, EM-MTR11001-195
Color	Black
Radiator Material	Brass / Black Chrome Plating
Radome Material	Elastomeric Polymer, Proprietary
Operating Temperature	-40° to 85° C
Corrosion	Salt Fog
Humidity	95%
Vibration	AAR & MIL-STD810E

\*Recommended NMO Mounts/Cable Assemblies sold separately.  
Performance may vary when using other manufacturer's (not recommended) NMO type mounts.

ELECTRO-MAGWAVE, INC.

10221 Sweet Valley Drive, STE 1 Valley View, OH 44125 † 216-453-1160 ‡ 216-447-8828 [www.emwaveinc.com](http://www.emwaveinc.com)