

# 20D-30DXC

## (60 RU) Outdoor Enclosure



### General

#### \*Approximate Weight

- 280 Lbs. assembled
- 430 Lbs. shipping weight

#### Doors

- 4, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with 3/8" aluminum filled gaskets
- 4 Auto door stops standard

#### Material

- .125" Alumiflex™
- Finish: Paint Cream
- RF properties: Non-ferrous

#### Vents

- 30 bottom louvers per door
- 20 top louvers – In top cover, under Alumishield™
- One removable filter panel per door
- 20 fixed filter pads in top cover

#### Handles

- Zinc Die Powder-coated Black EMKA Three Point Padlocking Handles

#### Lifting Hooks

- 4, standard

### Racking Specifications

#### Rails

- Four sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .125" Material (Alumiflex™)

#### Spacing

- 19" or 23" Racking standard

### Inside Clearance - Less Rails

#### Height

- 30.73"

#### Width

- 27.625" each side

#### Depth

- 18.75"

### Ratings

#### NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c) , NEMA 4X

#### Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

### Door Opening Clearance

#### Height

- 26.75"

#### Width

- 23.5"

### Exterior Cabinet Dimensions

#### Main Body

- Height: 30.98"
- Width: 59"
- Depth: 25"

#### Alumishield™

- Hang down height: 1.71"
- Width: 61.96"
- Depth: 27.67"

#### Handles

- Protrude 2.2"

#### Total Space Occupied

- Height: 31.605"
- Width: 65"
- Depth: 29.4"

\*\*\*Picture shown are examples only : See details for specifications\*\*\*



	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	26.75" – 30.98"	3.25"	21.50"
	26.57" – 26.75"	.18"	20.50"
	21.00" – 26.57"	5.57"	21.50"
Center	9.00" – 21.00"	12.00"	19.75"
	3.43" – 9.00"	5.57"	21.50"
	3.25" – 3.43"	.18"	20.50"
Bottom	0.00" – 3.25"	3.25"	21.50"