

RAK16-POE-A



- ↳ 19" patch panel surge protector for POE-B
- ↳ 32 ports
- ↳ In/Out front : RJ45
- ↳ Maintenance possible per port
- ↳ Secondary Protection
- ↳ UL497B

Installation		
Operating Temperature (Min)	°C	-40.0000
Operating Temperature (Max)	°C	85.0000
Operating Temperature (Min)	°F	-40.0000
Operating Temperature (Max)	°F	85.0000
Operating Relative Humidity (Max)	%RH	95
Operating Altitude (Max)	m	2000.0000
Operating Altitude (Max)	Ft	6500.0000
Housing/Enclosure material		aluminum
Mounting		Rack mount
IP Environmental rating (IP)		IP20
Installation Location		indoor
Product Dimension (L)	mm	483.0000
Product Dimension (H)	mm	88.0000
Product Dimension (L)	In	19.0200
Product Dimension (H)	In	3.4650
Miscellaneous		
Individual Pack		Yes
Storage Temperature (Min)	°C	-40.0000
Storage Temperature (Max)	°C	85.0000
Storage Temperature (Min)	°F	-40.0000
Storage Temperature (Max)	°F	85.0000
Installation		
Cable type		Ethernet
Electrical Characteristics		
Insertion loss		< 1 dB
Max. load current	IL	750 mA
Max. capacitance	C	< 25 pF (ligne ethernet)
Capacity (Maximum)	pF	< 25
Telecom Discharge Current (10/1000)	kA	0,05
Telecom Total Discharge Current (10/1000)	kA	0,05
Telecom Discharge Current (10/1000)	kA	0,05
Telecom Discharge Current (10/1000)	kA	0,05
Max Discharge Current (Imax (8/20µs x 1))	kA	0.0500
Mechanical Characteristics		
Technology		Diode écrêtage
Connection to Network		RJ45 female input/output
Mounting		Baie 19"
Housing material		Aluminium
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Dimensions		See diagram
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B / IEEE 802-3at
Part number		



RACKMOUNT DATA

DATALINE

RAK16-POE-A

6372

