

PFU-12-C-0-060-01



Power Extender, Universal Mount, Outdoor, 60 Watt, 12 Vdc, Fiber Pass Through

- Environmentally sealed closure - IP67
- Electrical power management
- Circuit protection electronics
- Automatically conditions electrical voltage to the correct level

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Power extender

General Specifications

Color	Aluminum
Mounting	Universal pole mount Universal wall mount
Total Ports, quantity	1
Transition Performance	1 port, 60W at 12 Vdc
Transmission Standards	CISPR 22/FCC CFR 47 EN300386/FCC CFR 47 ETSI EN 300 019-1-4 IEC 60950-1 IEC 60950-22 ITU-T K.45 NEC Class II
Transmission Standard Note	NEC Class II requires a power supply unit (PSU) limited to less than 60V DC

Dimensions

Height	224.71 mm 8.847 in
Width	283 mm 11.142 in
Depth	77.02 mm 3.032 in

Material Specifications

Finish	White solar shield
Material Type	Aluminum

Environmental Specifications

Installation temperature	-5 °C to +45 °C (+23 °F to +113 °F)
Operating Temperature	-40 °C to +65 °C (-40 °F to +149 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

PFU-12-C-0-060-01

Environmental Space	Outdoor
Qualification Standards	IEC 60529:2001, IP68
Safety Standard	CE CSA SELV

Packaging and Weights

Weight, net	5.08 kg 11.199 lb
--------------------	---------------------