

**SSH-M****SnapStak® Plus Adjustable Hanger for 15mm to 26mm Cable - No Grommets Required**

## Product Classification

Brand	SnapStak® Plus
Product Type	Hanger kit

## Dimensions

Compatible Diameter, maximum	26.000 mm		1.024 in
Compatible Diameter, minimum	15.000 mm		0.591 in
Height	67.10 mm		2.64 in
Length	48.60 mm		1.91 in
Width	38.00 mm		1.50 in

## Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

## Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
-----------------------	--------------------------------------

## General Specifications

Hanger Type	Snap-in hanger
Cables per Hanger	1
Color	Silver
CommScope Accessories	Hangers
Material Type	Stainless steel
Maximum Stack Height	2
Maximum Stack Height, Coaxial	3
Ordering Note	CommScope® standard product in the United States and Canada
Package Quantity	10

## Mechanical Specifications

Corrosion Resistance, minimum with no degradation	=1000 hours in salt spray chamber
Flammability Test Method	UL 2043
Mounting	3/4 in drilled cable ladder

SSH-M

Vibration Survival	=4 hours at resonant frequency
Environmental Strength Capability	Double cable weight

## Packed Dimensions

Height	330.2 mm   13.0 in
Length	260.4 mm   10.3 in
Shipping Weight	0.53 kg   1.17 lb
Width	63.5 mm   2.5 in

## Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

## \* Footnotes

Maximum Stack Height    Fiber, Hybrid, Power