

IBflex®

In-Building and Outdoor Network Testing

Scanning Receiver | 10 MHz – 6 GHz



The PCTEL® *IBflex* scanning receiver combines portability and accuracy with the power to test multiple technologies and bands simultaneously. It can be used to deploy 5G New Radio networks in sub-6 GHz spectrum, verify public safety coverage, optimize dense small cell deployments, and improve the reliability of IoT systems. Low power consumption and a hot-swap battery system make the *IBflex* scanner a convenient tool for a long day of walk testing or interference hunting.

Bands

- 5G: 3GPP FR1
- All existing 2G, 3G, and 4G
- CBRS
- Public safety
- WiFi (2.4 and 5 GHz)
- Other bands currently deployed around the world

Technologies

- 5G NR
- LTE FDD
- TD-LTE
- NB-IoT
- UMTS
- GSM
- CDMA
- EV-DO
- WiFi
- LAA
- P25
- DMR
- TETRA

Custom Channel Power Measurements for additional technologies

Features

- 4G/5G Dynamic Spectrum Sharing (DSS)
- Dual polarization beamforming measurements
- 2x2 and 4x2 LTE MIMO measurements
- Hot-swap battery system
- Windows® laptop and Android™ tablet support
- Connect with Bluetooth® or USB
- Blind Scan for automatic channel detection



IBflex[®] Specifications

5G New Radio (NR)

Measurement modes	NR TopN Signal: Synchronization channels (PSS/SSS) & PBCH; Layer 3 Reporting: MIB, SIB1; Dual polarization beamforming measurements; Blind Scan
Data modes	PCI, PSS-RP [dBm], SSS-RP [dBm], PSS-RQ [dB], SSS-RQ [dB], SS-CINR [dB], SSS-CINR [dB], RSPBCH-RP [dBm], RSPBCH-RQ [dB], RSPBCH-CINR [dB], SSB-RP [dBm], SSB-RQ [dB], SSB-CINR [dB], SSB-idx, SSB-RSSI, SSS-Delay Spread, Time Offset
Sub carrier spacing	15/30 kHz
Max. number of channels	12
Max. number of beams/channel	8
Measurement rate (typical)	30/sec
Dynamic range (CINR)	PSS/SSS CINR: -10 to +33 dB PBCH DMRS CINR: -8 to +40 dB
Min. detection level	RP SCS @15 kHz: -135 dBm, SCS @30 kHz: -132 dBm
Accuracy (CINR)	PSS/SSS, PBCH DMRS ±2 dB
Max. number of PCIs	16

LTE FDD and TD-LTE

Measurement modes	Top N Synchronization Channel Reference Signal (P-SCH/S-SCH) and Resource Block (Wideband, Subband), Dynamic Spectrum Sharing (DSS), Layer 3 Reporting, Blind Scan, Mobile Blind Scan
Data modes	RP, RQ, CINR, Cyclic Prefix, Time Offsets, Delay Spread; RF Path Measurements (4x1, 4x2); MIMO: Condition Number, ECQI, EPUT
Channel bandwidths	1.4 / 3 / 5 / 10 / 15 / 20 MHz
Max. number of channels	24
Receive modes	SISO; MIMO (2x2, 4x2)
Transmit antenna configurations	1, 2, 4 (with path measurement)
Measurement rates	Sync Channel RS LTE FDD: 50/sec; TD-LTE: 25/sec
Dynamic range (CINR) @ 10/15/20 MHz	RS P-SCH/S-SCH -26 to +40 dB -10 to +18 dB
Min. detection level	P-SCH/S-SCH & RS -140 dBm (RSRP @ 15 kHz)
Accuracy (CINR)	P-SCH/S-SCH & RS ±1 dB
Max. number of PCIs	16

NB-IoT

Measurement modes	Top N NRS (Narrowband Reference Signal), NPSS (Narrowband Primary Synchronization Signal), and NSSS (Narrowband Secondary Synchronization Signal), Layer 3 Reporting, Blind Scan
Data modes	NRS: RP, RQ, RSSI, CINR, Time Offset; NPSS: RP, RQ, RSSI, CINR; NSSS: RP, RQ, RSSI, CINR, Time Offset
Operation mode	In-Band, Guard Band, Stand-alone
Channel bandwidths	180 kHz
Measurement rates	5/sec
Dynamic range (CINR)	NRS -10 to +40 dB
Min. detection level	NRS RP -138 dBm
Accuracy (CINR)	NRS ±2 dB
Max. number of PCIs	16

UMTS [WCDMA/HSPA(+)]

Measurement modes	Top N Pilot, Layer 3 Reporting, Blind Scan, Mobile Blind Scan
Data modes	Io, Ec/Io, Aggregate Ec/Io, SIR, Rake Finger Count, Time Offset, Delay Spread
Channel bandwidths	200 kHz / 3.84 MHz
Max. number of channels	24
Measurement rate	100/sec (high speed mode); 50/sec (high dynamic range mode)
Top N CPICH dynamic range (Ec/Io)	-26 dB
Min. detection level	-120 dBm (high dynamic range mode)
Accuracy	±1 dB
Max. number of Pilots	32

GSM

Measurement modes	Color Code, Layer 3 Reporting, Blind Scan, Mobile Blind Scan
Data modes	BSIC, C/I, RSSI
Channel bandwidths	30 kHz / 200 kHz
Measurement rates	Up to 200 BSIC Decodes/sec
Dynamic range	+2 dB C/I
Min. basic detection level	-110 dBm
Accuracy	±1 dB

IBflex[®] Specifications

CDMA and EV-DO

Measurement modes	Top N PN, CDMA Layer 3 Reporting, Blind Scan, Mobile Blind Scan
Data modes	Ec, Io, Ec/Io, Aggregate Ec/Io, Pilot Delay, Delay Spread
Channel bandwidths	30 kHz / 1.25 MHz
Max. number of channels	24
Measurement rates	CDMA: 25/sec; EV-DO: 18/sec
Top N PN dynamic range, Ec/Io	CDMA: -28 dB; EV-DO: -18.5 dB
Min. PN detection level	CDMA: -130 dBm; EV-DO: -120 dBm
Accuracy (CINR)	±1 dB
Max. number of Pilots	32

WiFi

Wireless adapter	ORINOCO [®] USB-9100 (US), Asus USB-AC56 (world) or equivalent
Radio configuration	802.11a/b/g/n/ac
Data modes	Signal Strength, Noise Level, SNR, Channel Number, Channel Bandwidth, BSSID, Device Name, SSID, Security Protocol, 802.11 Media, Beacon Interval, Channel Utilization, Throughput
Frequency range	2.4 - 2.483 GHz; 5.15 - 5.85 GHz (subject to country regulations)
Measurement rates	9/sec (typical); 5/sec (typical) for 802.11ac

LAA

Measurement modes	QTopN
Data modes	RSRP, RSRQ, RS-CINR, PSS-RQ, PSS- RP, PSS-CINR, SSS-RP, SSS-RQ, SSS-CINR
Channel bandwidth	20 MHz
Max. number of channels	24
Measurement rate (20MHz, 1 Sig)	6.25/sec
Dynamic range (CINR)	-12 dB
Minimum detection level	RSRP -130 dBm
Accuracy (CINR)	RS-CINR ±1 dB (Input CINR 0 dB to +15 dB)

P25 (Phase 1 and Phase 2)

Measurement modes	DL (Phase 1 and Phase 2), UL (Phase 1), RSSI
Data modes	DL SINR, RSSI, OOS-BER, Frame BER, Network ID, Auto Classification of Phase and Modulation Type UL SINR, RSSI, Frame BER, Network ID, Mobile ID, Auto Classification of Phase and Modulation Type
Channel bandwidths	DL & UL 12.5 kHz
Measurement rate	DL 5.4 Decodes/sec (maximum); 2.7 Decodes/sec (typical); 100 RSSI/sec UL 2.4 Decodes/sec (typical), 100 RSSI/sec
Dynamic range (SINR)	DL & UL +1 dB minimum detection
RSSI Accuracy	DL (Phase 1 C4FM & Phase 2 HDQPSK) ±1 dB over -105 to -10 dBm UL ±1 dB over -105 to -10 dBm
SINR Accuracy	DL (Phase 1 C4FM & Phase 2 HDQPSK) ±1 dB over +10 to +25 dB; ±2 dB over +7 to +10 dB, 25 to 30dB UL ±1 dB over +10 to +25 dB; ±2 dB over +7 to +10 dB, 25 to 30dB
Adjacent channel rejection	DL & UL 49 dB

DMR

Measurement modes	Decode, RSSI
Data modes	SINR, RSSI, Frame BER
Channel bandwidths	12.5 kHz
Measurement rate	5.4 Decodes/sec (maximum); 2.7 Decodes/sec (typical); 100 RSSI/sec
Dynamic range (SINR)	-1 dB minimum detection
Accuracy	SINR ±1 dB over 6 to 40 dB; ±2 dB over 3 to 6 dB RSSI ±1 dB over -118 to -10 dBm
Adjacent channel rejection	49 dB

TETRA

Measurement modes	Decode, RSSI
Data modes	SINR, RSSI, Frame BER, Color Code, MCC, MNC
Channel bandwidths	25 kHz
Measurement rate	6.5 Decodes/sec (maximum); 3.5 Decodes/sec (typical); 100 RSSI/sec
Dynamic range (SINR)	+2 dB minimum detection
Accuracy	SINR ±2 dB over +8 to +20 dB; ±3 dB over +4 to +8 dB RSSI ±1 dB over -118 to -10 dBm
Adjacent channel rejection	20 dB

GPS

Type	56 channel internal receiver
Position accuracy	2.5 meters
Acquisition time	Cold start: <30 sec; Hot start: <2 sec
Sensitivity (tracking)	>-150 dBm

IBflex® Specifications

Power Measurements

Accuracy		±1 dB (across basic RF input power range)
Dynamic range		-120 to -20 dBm @ 30 kHz
RSSI	5G NR, LTE NB-IoT, UMTS, GSM CDMA, EV-DO	11,050 ch/sec (maximum, contiguous channels) 4,250 ch/sec (maximum, contiguous channels) 8,500 ch/sec (maximum, contiguous channels)
Custom channel power (examples)	12.5 kHz (P25, DMR, EDACS, Analog LMR) 25 kHz (TETRA, EDACS, Analog LMR) 125 kHz (LoRa) 250 kHz (LoRa) 500 kHz (LoRa)	25,500 ch/sec (maximum, contiguous channels) 14,025 ch/sec (maximum, contiguous channels) 10,710 ch/sec (maximum, contiguous channels) 8,925 ch/sec (maximum, contiguous channels) 6,885 ch/sec (maximum, contiguous channels)
Enhanced Power Scan (EPS)	5 kHz to 20 MHz in 2.5 kHz increments	1,000 MHz/sec @ 5 MHz (typical)
Spectrum analysis	Range: >90 dB	>270 MHz/sec (single sweep)
LTE power analysis	1.3 / 3 / 5 / 10 / 15 / 20 MHz TD-LTE only	20 msec @ 5 MHz

RF Characteristics

Frequency range		10 MHz - 6 GHz
Internally generated spurious response		-110 dBm (typical)
Conducted local oscillator		- 75 dBm max.
RF operating range	In-Band	- 15 dBm max.
Desensitization	Adjacent channel Alternate channel	>50 dB >55 dB
Safe RF input range		10 dBm
Frequency accuracy		±0.05 ppm (GPS Locked); ±0.1 ppm (GPS unlocked)
Intermodulation-free dynamic range		2 tone (level 2) @ -40 dBm, 6 GHz, -68 dBc (typical), -12.6 dBm TOI; @ -25 dBm, 6 GHz, -70 dBc (typical), 10 dBm TOI

Physical

Power switch		Normal and Power Save
Maximum power (+9 to +17 VDC)		18W; Power Save: 10W
Size	Without battery pack With battery pack	7.6" D x 4.4" W x 1.55" H (192 mm D x 111.8 mm W x 39.4 mm H) 10.1" D x 4.4" W x 2.1" H (257.6 mm D x 111.8 mm W x 53.1 mm H)
Weight	Without battery pack With battery pack	2.4 lb (1.1 kg) 3.8 lb (1.7 kg)
Temperature range		Operating: 0°C to +50°C; Storage: -40°C to +85°C
Humidity		5% to 95% relative humidity, non-condensing
Host data communications interface		USB 2.0, Ethernet, Bluetooth®
Data storage		SD (32 GB)
Antenna ports		RF: SMA Female (50Ω); GPS: Male (50Ω); Bluetooth: SMA Female (50Ω)
Safety		EN 62368-1
EMC		EN 301 489-1
Shock and vibration		MIL-STD-810G, SAE J1455
RoHS		Directive 2011/65/EU and amendment 2015/863 (RoHS 3)

Supported bands, technologies, data modes, software features, and frequency ranges vary by scanning receiver configuration. Upgrades may be available for previously purchased scanning receivers. Please contact a sales representative for more information.

Solving Complex Wireless Challenges

PCTEL is a leading global provider of wireless technology, including purpose-built Industrial IoT devices, antenna systems, and test and measurement solutions. Trusted by our customers for over 25 years, we solve complex wireless challenges to help organizations stay connected, transform, and grow.

For more information about the IBflex scanning receiver, contact your sales representative or visit pctel.com/scanning-receivers



PCTEL, Inc.

T: +1 301 515 0036 | pctel.com | NASDAQ: PCTI

Specifications subject to change without notice. PCTEL® and IBflex® are registered trademarks of PCTEL, Inc. Windows® is a registered trademark of Microsoft Corporation. Android™ is a trademark of Google Inc. Bluetooth® is a registered trademark of Bluetooth SIG. ORINOCO® is a registered trademark of Proxim Wireless Corporation. ©2021 PCTEL, Inc. All rights reserved. Rev R (February 2021)