

FHBDW-H2M22-0150F



HELIAX® FiberFeed® Discrete: Single mode 2 fiber drop assembly, hardened SC/APC to Ruggedized LC Duplex, Ericsson RRUS, ALU RRH, Nokia AirScale/Flexi (OCTIS), weatherproofing not included, 150 ft

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Wireless Fiber Cable Assemblies
Product Brand	FiberFeed® HELIAX®
Product Series	FHBDW
Ordering Note	CommScope® non-standard product

General Specifications

Interface, Connector A	SC/APC
Interface Body Style, connector A	Straight
Interface, Connector B	DLC
Interface Body Style, connector B	Straight
Jacket Color	Black
Total Fibers, quantity	2

Dimensions

Cord Length	45.72 m 150 ft
--------------------	------------------

Mechanical Specifications

Minimum Bend Radius, furcation	61 mm 2.402 in
---------------------------------------	------------------

Optical Specifications

Fiber Type	G.657.A2
Assembly Insertion Loss, typical	0.75 dB
Assembly Insertion Loss, typical note	Insertion loss is measured at 1310 and 1550 nm

FHBDW-H2M22-0150F

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	Outdoor

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



* Footnotes

Assembly Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)