

698-960-1700-2690 MHz 3.2-3.4 dBi Omni LTE Stick Antenna with 2x N Plugs



Designed for outdoor wireless networks operating in the LTE / 4G / 5G frequency ranges. This antenna is ideal for outdoor voice and data transmission deployments in remote, rural, industrial, utility and donor antenna deployments. *Every Ventev antenna is covered by the company's two-year TerraNet warranty program.*

For more information or to purchase, contact Ventev:
800.851.4965 or sales@ventev.com.

SPECIFICATIONS

Sku: 221383

Product Number: M3032034O21207

Dimensions: 24.5" x 1.25"

Construction: Fiberglass radome

Weight: 3 lbs.

Average Gain (both ports): 3.2 dBi / 3.4 dBi

Horizontal Beamwidth: 360

Vertical Beamwidth: 60 / 50

Impedance: 50 Ohms

VSWR: ≤ 2.5

Polarization: Vertical

Operating Temperature (F): -40 to 140 degrees

Max Power Rating: 50 Watts

Lead Number and Type: 2x 12" RG-58 leads

Connector Number & Type: 2x N Plugs

Radome Color: Gray

Mount Method: Mast mount with U-bolts that fit masts up to 3" diameter. Position antenna radome up.

Intrusion Prevention: IP54 compliant

FEATURES AND BENEFITS

- Two antenna leads connect with both the Primary and Diversity ports on the modern cellular modems, eliminating the need for two antennas
- Durable, fiberglass radome withstands the harshest environmental conditions
- Includes a heavy-duty L-bracket for mast mounting

698-960-1700-2690 MHz 3.2-3.4 dBi Omni LTE Stick Antenna with 2x N Plugs

Two Lead LTE Stick Omni Radiation Patterns

Vertical Patterns

Horizontal Patterns

