



SPECIFICATIONS

For patents see www.cf-pat.com

| | |
|-------------------------------|--|
| General | PIM Shield Cable Support Bars provide a low passive intermodulation mounting system to secure multiple Hybrid or Plastic Snap-ins (sold separately) in high risk PIM zones. The 901167-02-3 kit includes 3x 900353-02 Pole Mount Kit and 3x 900355 Extra Bar Kit combined together into a convenient site pack for 3-sector sites. |
| Grip range | 2.37-inch to 4.5-inch OD pipe (2-inch to 4-inch nominal pipe) |
| Snap-In mounting holes | 44 snap-in mounting holes per installation, 0.75-inch diameter |
| Bar dimensions | 2 bars per installation, 30.5 -inch x 3.9-inch x 0.14-inch thick |
| Hardware size | 1/2-13 UNC, 18-inch Threaded Rod length |
| System PIM performance | IM3 <-100 dBm when tested in accordance with proposed IEC 62037-8, near field test, 2x 20W test tones, while subjected to dynamic stimulus. To achieve specified PIM performance, torque hardware to 20 FT-LB (ConcealFab tool 900413) |
| Material | Galvanized Steel |
| Operating temperature | -40°C to +70°C |
| Shipping dimensions | 6.5-inch x 4.5-inch x 32-inch |
| Shipping weight | 39.0 lb. |