

Electrical Cabinet 120/240 Vac 60A Main 2x 20A Field Configurable Branches, MOV SPD, 15A 240V 2-Pole Breaker, UL67 Service Entrance Rated

SC-2MMA9-7602-NM101

60A Main Breaker, No ST, MOV SPD, 15A 240V Breaker, 2x20A



Features

- UL67 Listed
- · Suitable for use as service equipment
- 60A Main Breaker
- 2x 20A Factory Loaded Field-Configurable Branch Breakers
- 2 Open Field-Configurable Branch Breaker Locations
- Integral surge protection protects all downstream equipment
- 15A 240V 2-Pole Breaker Auxiliary Outlet
- Versatile Wiring Access
- Pole Mount or Wall Mount (external pole mount kit SC-POLE-KIT sold separately)
- · Padlock hasp for physical security

Applications

- · Small Cells
- Pico Cells
- · Micro Cells
- Macro Cells

- 5G Nodes
- DAS Systems
- Load Expansion

Description

Small cell/5G/DAS electrical power protection cabinet (also known as power distribution box) SC-2MMA9-7602-NM101 from Transtector, is a UL67 Listed service entrance rated power distribution box that accepts a 120/240 Vac split-phase electrical service, and distributes power from a 60A main breaker to individual loads via 12 field configurable 1 – 25A branch circuit breaker positions. Transtector electrical cabinets are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltage		120/240		Vac
Maximum Continuous Operating Volt	age (MCOV)			
L-L			350	Vac
L - N			175	Vac
SCCR (Short Circuit Current Rating)			10	kAIC
Main Breaker Rating		60		А
Branch Breaker Rating		2x 20A		А
Auxiliary Branch Power		15A 240V 2-Pole Breaker		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Electrical Cabinet 120/240 Vac 60A Main 2x 20A Field Configurable Branches, MOV SPD, 15A 240V 2-Pole Breaker, UL67 Service Entrance Rated SC-2MMA9-7602-NM101



Electrical Cabinet 120/240 Vac 60A Main 2x 20A Field Configurable Branches, MOV SPD, 15A 240V 2-Pole Breaker, UL67 Service Entrance Rated

SC-2MMA9-7602-NM101

60A Main Breaker, No ST, MOV SPD, 15A 240V Breaker, 2x20A



Surge Protection Specification

Minimum	Typical	Maximum	Units
	MOV SPD		
	L-L, L-N		
	20	75	kA
		1,200	Vpk
		600	Vpk
ng)	200		kAIC
		MOV SPD L-L, L-N 20	MOV SPD L-L, L-N 20 75 1,200 600

Mechanical Specifications

Size

 Outer Height
 14.25in
 [361.95 mm]

 Outer Width
 9.2 in
 [233.68 mm]

 Outer Depth
 6.32 in
 [160.53mm]

 Enclosure Material and Plating
 Steel

Installation

Humidity

Wall or Pole Mount Mount Type Service Wiring Terminals Compression Lug #3 AWG to #8 AWG **Branch Wiring Terminals** Compression Lug #4 AWG to #18 AWG SPD Status Indication Terminals 3-Pin Connector #22 AWG to #16 AWG **Environmental Specifications** Temperature (Operating Range) -20 to +55 deg C Temperature (Storage Range) -40 to +65 deg C **NEMA Rating** 3R

Compliance Certifications

UL Listed UL67 (Suitable for use as a service equipment)

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Electrical Cabinet 120/240 Vac 60A Main 2x 20A Field Configurable Branches, MOV SPD, 15A 240V 2-Pole Breaker, UL67 Service Entrance Rated SC-2MMA9-7602-NM101

90% non-condensing



Electrical Cabinet 120/240 Vac 60A Main 2x 20A Field Configurable Branches, MOV SPD, 15A 240V 2-Pole Breaker, UL67 Service Entrance Rated

SC-2MMA9-7602-NM101

60A Main Breaker, No ST, MOV SPD, 15A 240V Breaker, 2x20A



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Electrical Cabinet 120/240 Vac 60A Main 2x 20A Field Configurable Branches, MOV SPD, 15A 240V 2-Pole Breaker, UL67 Service Entrance Rated SC-2MMA9-7602-NM101

URL: https://www.transtector.com/electrical-cabinet-split-phase-120-240-vac-sc-2mma9-7602-nmd01-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

SC-2MMA9-7602-NM101 CAD Drawing

