



These antennas are extreme environment versions of our popular OD Series Antennas.

The MOD Series are special Marine/Sea Water resistant antennas with external metal fittings specially protected for the typical sea or harbor environment. The mount assembly and the base of the antenna are powder coated, with other mounting hardware being stainless steel.

For very high vibration environments (mining, quarry and oil field construction) the OD-MOD2 series provides a viable solution for a wide area network.

The feed assembly is made of machined aluminum components and is irradiated for weather protection.

Both series are colinear arrays and provide uniform omnidirectional coverage. Unique phasing cancels out-of-phase current distribution, improving performance.

Omni-directional, High Vibration & Marine, 2.4 GHz

- Uniform omni-directional coverage
- Marine versions provide powder coat finish with stainless steel hardware
- High vibration models have conformal foam dampening for heavy mining & construction

Model #	Frequency	Gain
MOD3-2400-WHT	2400-2485	3 dBi
MOD6-2400-WHT	2400-2485	6 dBi
MOD9-2400-WHT	2400-2485	9 dBi
MOD12-2400-WHT	2400-2485	12 dBi
MOD series is only available in White		
High Vibration Products		
OD3-2400MOD2-BLK	2400-2485	3 dBi
OD6-2400MOD2-BLK	2400-2485	6 dBi
OD9-2400MOD2-BLK	2400-2485	9 dBi
OD5-2400/5500MOD2-BLK	2400-2485 & 5150-5925	5 dBi
<u>Color options available for the OD-MOD2 series</u> WHT-White or BLK-Black		
OD-WMK	Wall Mount Bracket	

Specifications			
Frequency & Gain:	See above	Antenna Diameter:	1" (25 mm)
VSWR:	2:1 max over band	Length/Weight:	
Nominal Impedance:	50 ohms	2400/5500 Model	13", 2.5 lbs (33 cm, 1.1 kg)
Max. Power (continuous):	100 watts	3 dBi Models	14", 1.5 lbs (36 cm, 0.7 kg)
Vertical Beamwidth (-3 dB point):		6 dBi Models	17", 1.5 lbs (43 cm, 0.7 kg)
3 dBi Models	55 degrees	9 dBi Models	29", 2.0 lbs (74 cm, 0.9 kg)
6 dBi Models	25 degrees	12 dBi Model	41", 2.5 lbs (104 cm, 1.1 kg)
9 dBi Models	14 degrees	Material:	
12 dBi Model	7 degrees	MOD Marine Series	White Fiberglass radome with Powder Coat aluminum
2400/5500	22/30 degrees	OD-MOD2 Series	Black or white fiberglass with irradiated aluminum
Rated Wind Velocity:	120+mph (200+kph)	Shock & Vibration:	EN 300 019-2-4, IEC 60068
Lightning Protection:	External suggested	Water Ingress:	IPx5
Connector:	N female connector		
Mounting Kit:	Mast mount kit included		
	Wall Mount Bracket Optional (OD-WMK)		
Mounting Dimensions:	Mast up to 2.5" D (64mm)		