



Rapid Fiber™ EFDT NID Wall Mounting Fiber Box, outdoor, 12 SC /APC, 8-way splitter

- Designed to provide a quick and simple solution for installing fiber in small and medium sized MDU's
- Incorporates a unique fiber cable spooling system that stores up fiber cable within the enclosure
- Removes the need for field termination and extensive site survey inspections
- Weatherproof housing suitable for external environmental conditions

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Fiber wall box
Product Brand	Rapid Fiber™
Product Series	EFDT

General Specifications

Functionality	Patching Splitting
Access	Front
Distribution Type	1 x 8 splitter
Enclosure Color	Gray
Front Cover Type	Hinged with lock
Interface, Input	SC
Interface Feature, Input	APC
Mounting	Wall
Port, quantity	12
Split Ratio	Symmetrical
Splitter, quantity	1

Dimensions

Height	264.16 mm 10.4 in
Width	179.07 mm 7.05 in
Depth	71.12 mm 2.8 in

Material Specifications

760235625 | EFDT-NID-1181528

Enclosure Material Type LSZH thermoplastic

Optical Specifications

Fiber Mode Singlemode

Fiber Type G.657.A2

Wavelength Range 1260–1650 nm

Insertion Loss, Splitter, maximum 11 dB

Return Loss, Connector, minimum 55 dB

Environmental Specifications

Environmental Space Outdoor

Qualification Standards IEC 60529, IP55 | IEC 61753-1, category G

Packaging and Weights

Packaging quantity 8

Packaging Type Box | Carton

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

