

## L-864 / L-810 Red Single with Infrared (IR)




Dialight is the market leader in LED obstruction solutions with over 20 years of design and manufacturing experience. Dialight offers the industry's most reliable, energy-efficient and comprehensive line of LED-based obstruction systems in the world. Precision patented optics ensure maximum safety with minimal ground scatter for community friendly illumination. Dialight systems offer a small, light-weight flash head for ease of installation, and our low-maintenance fixtures virtually eliminate tower climbs and unplanned site visits for years, dramatically reducing maintenance costs and non-compliance risk. Dialight controlled LED obstruction solutions can be seamlessly integrated into existing operation and control centers while providing additional valuable information, both locally and remotely.

### Certifications & Compliance

- FAA AC 150/5345 - 43J
- FAA EB No. 67D & 98
- IP66/NEMA 4X
- ICAO Annex 14
- DGAC Mexico
- Transport Canada Standard 621

### A1 Tower



### Standard Features

- 5 year warranty
- ETL verified to FAA standards
- Superior surge and lightning protection
- Patented optics for minimal down light / ground scatter
- Remote monitoring options available

### D5C-KIT-STD-A1A Obstruction Lighting System Kit

This kit, supplied on a pallet, provides all the necessary lighting and hardware to install a new Dialight Vigilant A1 system on a tower 150ft–350ft (46m–107m).


Component P/N	Description	Qty
D6C-B77C-CTR	Red Beacon L-864/L-810 Controller	1
D664-R13-001	Red Beacon L-864 + IR	1
RT0-CR27-001	Single Side Marker L810 Red + IR	3
D256-6000PEC	Photocell, 3/4" NPT, Cast Enclosure	1
CAB-050183	Photocell Cable, 50ft, 18 AWG / 3 Conductor	1
CAB-300163 -AC	Side Marker Cable, 300ft, 16 AWG / 3 Conductor	1
CAB-450143-BFAC	Red Beacon Cable, 450ft, 14 AWG / 3 Conductor	1
D1RW-HDWR-E1	A1 Hardware Kit (L-810 Mounts, Junction Box, Hardware, and Tape)	1

**Specifications D5C-KIT-STD-A1A System Kit**

**A1 COMPLETE SYSTEM KIT**  
 Order Code: **D5C-KIT-STD-A1A**  
 Weight: 1 pallet/skid 398 lbs  
 Dimensions: 48 x 48 x 31"



Controller	Power Input
<b>D6C-B77C-CTR</b> <b>L-864/L-810 Controller</b> 13.67 x 12.40 x 5.39" 16 lbs (7.3 kg) IP66, NEMA 4X	Power input 120–240 VAC Power factor > 0.9 Frequency 50–60 Hz



Lighting	Effective Light Intensity
<b>D664-R13-001</b> <b>L-864 Red Beacon</b> 18.0 lbs (8.2 kg) IP66, NEMA 4X (13.25 bolt circle)	Red = 2,000 cd IR = 246 mW/sr
<b>RTO-CR27-001</b> <b>L-810 Single Side Marker</b> 2.0 lbs (0.91 kg) IP66, NEMA 4X	Red = 32 cd IR = 4 mW/sr



Cables
<b>CAB-450143-BFAC</b> <b>450 ft Red Beacon Cable</b> 14 AWG 3 conductors UL and CSA
<b>CAB-300163-AC</b> <b>300 ft Side Marker Cable</b> 16 AWG 3 conductors UL and CSA



Photocell	Spec
<b>D256-6000PEC</b> <b>Photocell</b> 2.0 lbs (0.91 kg) IP66, NEMA 4X	<ul style="list-style-type: none"> <li>• Long life (10+ years)</li> <li>• No adjustments required</li> <li>• Flat or conduit 3/4" NPT mounted</li> </ul>

<b>CAB-050183</b> <b>50 ft Photocell Cable</b> 18 AWG 3 conductors UL and CSA
---

<b>Relay Alarm Status</b>
Photocell: Day / Night Mode Detection
<b>Individual Alarms</b>
Photocell: Fail and Transition
L-864: Individual Fail Detection
L-810: Individual Fail Detection