



## VEHICULAR 4-PORT MIMO ANTENNA

**VLQ69273**

**698-960 / 1710-2700 / 2300-2700 / 4900-5900 MHZ + GPS MIMO ANTENNA**

The TE vehicular 4-port MIMO antenna covers the 698-960 / 1710-2700 MHz, 2300-2700 / 4900-5900 MHz as well as GPS (1575.42 MHz) frequency ranges. Configured with 3-port, dual-band elements in addition to 1-port with integrated GPS. Connector options include SMA male connectors for 3G/4G LTE and GPS ports with an RSMA male connector for the WiFi port. The housing incorporates a low-profile, rugged design that meets IP67 standards. The antenna also features high impact, UV-resistant polycarbonate plastic available in black or white.

### SPECIFICATIONS

PARAMETER	PERFORMANCE			
Model Number	VLQ69273B21G-518A (Black)		VLQ69273W21G-518A (White)	
No. of Ports	4 (2-ports 3G/4G LTE, 1-port WiFi, 1-port GPS)			
	3G/4G Port		WiFi Port	
Frequency Bands (MHz)	698-960 MHz	1710-2700 MHz	2300-2700 MHz	4900-5900 MHz
Peak Gain * dBi	3.3	4.6	5.5	5.3
Max Gain +/- 30 above horizon	N/A	N/A	N/A	4.1
VSWR* Typical	< 1.8:1	< 1.8:1	< 1.6:1	< 1.7:1
VSWR * Max	< 2.0:1			
Typical Port-to-Port Isolation *				
LTE1-to-LTE2>	15 dB			
LTE1-to-WiFi>	18 DB			
LTE2-to-WiFi>	20 DB			

\*Measured on 1 ft. (30.48 cm) diameter ground plane

PARAMETER	PERFORMANCE
Nominal Impedance	50 Ohm
Polarization	Vertical Linear
Azimuth Beam Width	Omnidirectional
Input Power, Max	50 Watt (ambient temp. of 25°C / 77°F)
Operating Temperature	-30° C - +70° C (-22°F to +158°F)
Dimensions (dia. x hgt)	132 mm x 75 mm (5.2" x 2.9")
Weight	0.95 kg (2.09 lb)
RF Connector	SMA-Male (3G/4G port) RSMA-Male (WiFi port)
Cable (exposed length)	LMR195M- 518.2 cm (17 ft)
Radome / Baseplate Material	PC, UL94 - V0 Rating, UV Stable (Black & White)
Material Compliance	ROHS compliant
IP Dust & Water Ingress Rating	IP67

\*Measured on 1 ft. (30.48 cm) diameter ground plane

## GPS ANTENNA SPECIFICATIONS

PARAMETER	PERFORMANCE
Frequency Band	1575.42 MHz (GPS L1)
Band Width	6 MHz (Typical)
Amplifier Gain	27 dB ± 3 dBc
Nominal Impedance	50 Ohm
Output VSWR	< 1.5:1
DC Voltage	2.7 - 12 Vdc
DC Current	20 mA (Nominal); 30 mA (-40°C - +85°C)
Out-of-Band Signal Rejection	> > 40 dB rejection @ ± 50 MHz from center frequency
Intermodulation@ CW Mode (-40°C - +85°C)	Int1 Int2 IM3
Power, dBm	-10(1842.8 MHz) -10(2110 MHz) -100(1575.6 MHz)
Power, dBm	-10(829.58 MHz) -10(2405 MHz) -100(1575.42 MHz)
Power, dBm	-10(755.42 MHz) -10(820 MHz) -100(1575.42 MHz)
Input 1 dB Compression @ 750 MHz, 2000 MHz & 3500 MHz	>10 dBm (-40°C - +85°C)
RF Connector	SMA-Male
Cable (exposed length)	RG174-518.2 cm (17ft)

## PART NUMBER

VLQ69273B2ING-518A	2-Ports 4G/LTE, 1-Port GPS: SMA Male; 1 Port WiFi:RSMA Male(Black)
VLQ69273W2ING-518A	2-Ports 4G/LTE: SMA Male; 2 Ports WiFi:RSMA Male(White)

### TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

### te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

05/25 Original