


760127407 | R-024-DZ-5K-FSUAQ

LazrSPEED® Riser Distribution Cable, interlocking aluminum armored with riser jacket, 24 fiber single-unit

Representative Image



General Specifications

Cable Type	Distribution
Construction Type	Armored
Subunit Type	Gel-free

Construction Materials

Fiber Type Solution	LazrSPEED® 550, 50 µm multimode fiber (OM4)
Total Fiber Count	24
Armor Type	Interlocking aluminum
Fiber Type	LazrSPEED® 550, 50 µm multimode fiber (OM4)
Fiber Type, quantity	24
Jacket Color	Aqua

Dimensions

Cable Weight	131.0 lb/kft 195.0 kg/km
Diameter Over Armor	13.34 mm 0.53 in
Diameter Over Jacket	15.40 mm 0.61 in

Physical Specifications

Minimum Bend Radius, loaded	30.7 cm 12.1 in
Minimum Bend Radius, unloaded	21.5 cm 8.5 in
Tensile Load, long term, maximum	90 lbf 400 N

760127407 | R024-DZ-5K-FSUAQ

Tensile Load, short term, maximum 300 lbf | 1335 N
Vertical Rise, maximum 209.0 m | 685.7 ft

Flame Test Specifications

Flame Test Listing NEC OFCR (ETL) and c(ETL)
Flame Test Method UL 1666

Environmental Specifications

Environmental Space Riser
Installation Temperature -20 °C to +70 °C (-4 °F to +158 °F)
Operating Temperature -20 °C to +70 °C (-4 °F to +158 °F)
Storage Temperature -40 °C to +70 °C (-40 °F to +158 °F)

Mechanical Test Specifications

Compression 485 lb/in | 85 N/mm
Compression Test Method FOTP-41 | IEC 60794-1 E3
Flex 25 cycles
Flex Test Method FOTP-104 | IEC 60794-1 E6
Impact 25.80 ft lb | 35.00 N-m
Impact Test Method FOTP-25 | IEC 60794-1 E4
Strain See long and short term tensile loads
Strain Test Method FOTP-33 | IEC 60794-1 E1
Twist 10 cycles
Twist Test Method FOTP-85 | IEC 60794-1 E7

Environmental Test Specifications

Heat Age -20 °C to +85 °C (-4 °F to +185 °F)
Heat Age Test Method IEC 60794-1 F9
Low High Bend -20 °C to +70 °C (-4 °F to +158 °F)
Low High Bend Test Method FOTP-37 | IEC 60794-1 E11
Temperature Cycle -20 °C to +70 °C (-4 °F to +158 °F)
Temperature Cycle Test Method FOTP-3 | IEC 60794-1 F1

Qualification Specifications

Cable Qualification Standards ANSI/ICEA S-83-596 | Telcordia GR-409

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



760127407 | R-024-DZ-5K-FSUAQ

Included Products

CS-5K-TB (Product Component—not orderable) — LazrSPEED® 550 OM4 Bend-Insensitive Multimode Fiber

* Footnotes

Operating Temperature Specification applicable to non-terminated bulk fiber cable