



High Density 1U Sliding fiber Splice Panel, accepts (4) G2 modules or MPO panels, providing up to 48 duplex LC ports, or up to 32 MPO port, accepts splice wallets, RoloSpice trays and stackable splice trays

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber splice panel
Product Series	HD

General Specifications

Color	Black Silver
Color, front	Silver
Color, rear	Black
Intelligence Type	iPatch® ready
Rack Type	EIA 19 in
Rack Units	1
Shelf Movement	Sliding

Dimensions

Height	44.45 mm 1.75 in
Width	450.85 mm 17.75 in
Depth	505.46 mm 19.9 in
Material Thickness	0.9 mm 0.035 in

Material Specifications

Material Type	Steel
----------------------	-------

Environmental Specifications

760231506 | HD-1U-SP

Safety Standard UL

Packaging and Weights

Packaging quantity 1

Weight, net 11.85 lb | 5.375 kg

Regulatory Compliance/Certifications

Agency

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

Classification

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant

