SHK-78-2-P



Single Hanger Kit for 7/8 in coaxial cable, double stack; includes hardware and angle adapter

Product Classification

Product TypeHanger kitProduct BrandValuSite™

Ordering Note CommScope® standard product in Asia Pacific | CommScope®

standard product in Mexico, Central America, and South America

General Specifications

Cables per Hanger 2

Color Black

Hanger Type Composite clamp

Harmonized System (HS) Code 854420 (Coaxial cable and other coaxial electric conductors)

Mounting M8 hardware

Dimensions

Height 101.6 mm | 4 in

Maximum Stack Height 2

Width 26.162 mm | 1.03 in

Length 60.198 mm | 2.37 in

Compatible Diameter, maximum 28.194 mm | 1.11 in

Compatible Diameter, minimum 26.67 mm | 1.05 in

Nominal Size 7/8 in

Electrical Specifications

Return Loss Effect 0.1 dB

DTF Effect 0.1 dB

Material Specifications

COMMSCOPE®

SHK-78-2-P

Material Type Engineered plastic | Stainless steel

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+85 \,^{\circ}\text{C}$ ($-40 \,^{\circ}\text{F}$ to $+185 \,^{\circ}\text{F}$)

Corrosion Resistance, minimum with no degredation ≥500 hours in salt spray chamber

Environmental Strength Capability Double cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

 Height, packed
 15 cm | 5.906 in

 Width, packed
 15 cm | 5.906 in

 Length, packed
 3 cm | 1.181 in

Included Angle adapter | Hardware

Packaging quantity

Weight, gross 0.45 kg | 0.992 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power