

# FHBDW-H2M22-0035F

---



HELIAX® FiberFeed® Discrete: Single mode 2 fiber drop assembly, hardened SC/APC to Ruggedized LC Duplex, Ericsson RRUS, ALU RRH, Nokia AirScale/Flexi (OCTIS), weatherproofing not included, 35 ft

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America
<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Wireless Fiber Cable Assemblies
<b>Product Brand</b>	FiberFeed®   HELIAX®
<b>Product Series</b>	FHBDW
<b>Ordering Note</b>	CommScope® non-standard product

## General Specifications

<b>Interface, Connector A</b>	SC/APC
<b>Interface Body Style, connector A</b>	Straight
<b>Interface, Connector B</b>	DLC
<b>Interface Body Style, connector B</b>	Straight
<b>Jacket Color</b>	Black
<b>Total Fibers, quantity</b>	2

## Dimensions

<b>Cord Length</b>	10.67 m   35.007 ft
--------------------	---------------------

## Mechanical Specifications

<b>Minimum Bend Radius, furcation</b>	61 mm   2.402 in
---------------------------------------	------------------

## Optical Specifications

<b>Fiber Type</b>	G.657.A2
<b>Assembly Insertion Loss, typical</b>	0.75 dB
<b>Assembly Insertion Loss, typical note</b>	Insertion loss is measured at 1310 and 1550 nm

# FHBDW-H2M22-0035F

---

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +70 °C (-40 °F to +158 °F)
<b>Environmental Space</b>	Outdoor

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant



## \* Footnotes

**Assembly Insertion Loss, typical note** Insertion loss is measured at a room temp of +20°C (+68°F)