



YS6CFXLTCKITC

by Burndy
Catalog ID: YS6CFXLTCKITC

Prop 65 Notice

Electro-tin plated copper compression reducer/splice, with a through hole for cable inspection on each side, for 6 AWG wire.

Product Details

General

Color Code	Blue
Connector Type	Splice
Die Index	7;24
Feature - Barrel Type	Standard
Material	Copper
Plated	N
Plating Type	Unplated
Temperature Rating	194
Trade Name	HYSPLICE™
UPC	781810346457
UPC 12 Digit	7818103464577

Dimensions

Dimension - B Length inch	0.73 in
Dimension - L Length Overall mm	40.64 mm
Dimension - Length BB inch	0.73 in
Dimension - Length Overall inch	1.6 in
Dimension - Strip Length inch	0.70 in

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600
Voltage - Maximum	35000

Conductor Related

Conductor - Copper Flex G Size A	6 AWG
Conductor - Copper Flex G Size B	6 AWG
Conductor - Copper Flex H Size A	6 AWG
Conductor - Copper Flex H Size B	6 AWG
Conductor - Copper Flex I Size A	6 AWG
Conductor - Copper Flex I Size B	6 AWG
Conductor - Copper Flex K Size A	6 AWG

Conductor - Copper Flex K Size B	6 AWG
Conductor - Copper Flex M Size A	6 AWG
Conductor - Copper Flex M Size B	6 AWG
Conductor - Copper Str Size	6 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	25
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)