

EM-M11001-195

NMO 3/4" Hole Mount Assembly



- Low Profile
- Ease of installation: Designed for a one-operator installation from above surface
- All brass components with silver plated contact
- Heavy Duty mounting claw for reliable contact and ground connections
- Premium double shielded foam PE, low loss 195 type cable

Electrical Specifications

Frequency Band	30 – 1000 MHz
VSWR ¹	1.5:1 typical
Impedance	50Ω
Cable Insertion Loss	2 dB, max
Power Rating ²	100 W @1000 MHz

Mechanical Specifications

Mounting Height	0.375 in. (9.5 mm)
Mounting Hole	0.75 in. (19.05 mm)
Outside Mounting Diameter	1.13 in. (28.7 mm)
Mounting Application / Type	Thru-hole
Cable ³	Low Loss 195 type
Cable Length	17 ft. (5.1 m)
Connector Type	Sold separately
Mounting Material	Brass
Operating Temperature Range	-40° to 85° C
Mounting Surface Weather Seal	O-Ring
Corrosion	Salt Fog
Humidity	95%

1. Antenna / Frequency Dependent 2. VSWR, Temperature and Altitude Dependent 3. Other cable types available upon request

ELECTRO-MAGWAVE, INC.

10221 Sweet Valley Drive, STE 1 Valley View, OH 44125 † 216-453-1160 ‡ 216-447-8828 www.emwaveinc.com