

Y(B)1505

Directional Yagi Antenna

GOLD ANODIZED YAGI ANTENNAS SURE LONG-TERM PERFORMANCE

TE's premium series Directional Yagi antennas are fully gold anodized for corrosion resistance. Our engineering staff has also optimized the product family for forward gain by computer analysis and then field-tested each for conformance.

FEATURES AND BENEFITS

- Every Yagi is tuned on a network analyzer for best power match and lowest VSWR.
- All Yagi antennas ship complete with a high quality cast aluminum mounting kit that includes stainless steel hardware and allows vertical or horizontal orientation during installation. (VHF models require light assembly)
- Available in gold or black (B) anodized finish

APPLICATIONS

- Point to point directional and multiple point to omnidirectional outdoor antennas applications used by private organizations and government agencies around the globe
- Typical applications include transportation such as railroad switching, remote locations reporting examples that include oil fields and weather conditions and meter data transmissions for utilities

MECHANICAL SPECIFICATION


Material	Aluminum
Length	72"
Height	39.5"
Boom Diameter	1.25"
Weight	6 lbs
Rated Wind Velocity	150mph (241kph)
Equivalent Flat Area	0.9102 sq. ft.
Cable	None
Termination	N-Female connector
Color	Gold or Black Anodized
Lightning Protection	Lightning Arrestor LABH350NN (Sold Separately)
Mounting	Heavy duty gold cast (Kit included as shown)

ELECTRICAL SPECIFICATION


Frequency Range	150 – 174 MHz (Tunable)
VSWR	< 2:1
Return Loss	-10dB max
Nominal Gain	9.2 dBd
Front to Back Ratio	20 dB
Maximum Power	300 W
Nominal Impedance	Ω 50
Polarization	Vertical or Horizontal
Pattern	Directional
Horizontal Beamwidth (For Horizontal Polarization)	60°
Vertical Beamwidth (For Vertical Polarization)	54°
Tuning	See cut chart
Transmitting/Receiving	Both



Heavy-Duty Mounting Kit Included



Vertical-to-Vertical Polarization
Azimuth Pattern (Y, Z, or E-plane)



Horizontal-to-Horizontal Polarization
Azimuth Pattern (Y, Z, or H-plane)

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

05/25 Original