



WPS-7

Weather Protection System: 1-5/8" to 1/2" Connections



[Installation video](#)



[Installation instructions](#)



[WPS cross-reference chart](#)



Contact technical support:
1-888-201-6073
techsupport@jmawireless.com

General	Specification	Comment
Cables supported	Andrew AVA7, AVA7RK, AL7, VXL7, LDF76 RFS LCG158 Eupen EC7 NK Draka RFA158 LS/Superior Essex LHF 42D, LHF-42DUF Rosenberger SL 1-5/8" R	
Dimensions in. (mm)	5.00 x 3.20 (127 x 81.3)	
Weight	0.64 lb 290 g	
Material	1-5/8" - Silicone Rubber 1-5/8" to 1/2" Adapter- U.V. Stable ABS	
Lubricant	Dow Corning Molykote® III	
Reusability	Unlimited	

Environmental	Specification	Comment
Installation temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Operating temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Moisture resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion resistance	1000 hours	ASTM B117
U.V. resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 hours	
Fire rating	UL94 HB	

07/03/19

