



S9025PL/S9025PR

Mini RFID Panel Antenna 902-928 MHz

S9025PL and S9025PR are high-performance RFID antennas and the only UHF RFID antenna available to the market that offers no-compromise performance in a small package. At only 5.2" square, the antenna offers a gain specification of 5.5 dBic and axial ratio better than 2 dB. In effect, the antenna is providing the performance one would expect of a much larger antenna. The antenna is not only mechanically robust but is less likely to be exposed to excessive damage by virtue of its reduced size.

FEATURES AND BENEFITS

- Circularly polarized
- Low VSWR and axial ratio
- Rugged, ultra-heavy-duty construction
- IP67-rated
- Left-hand and right-hand CP versions
- Weather and UV resistant radome
- High performance in a small package
- Wide range of connector and cable options

APPLICATIONS

- Warehouse
- Distribution center
- Airports and hospitals
- Transit terminals
- Conveyer belt

ELECTRICAL SPECIFICATIONS

Antenna Model	S9025PR/S9025PL
Operating Frequency (MHz)	902 - 928
VSWR - Max	1.5:1
Gain (dBic)	5.5
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	10
Polarization	Circular RH or Circular LH
Horizontal Plane 3 dB Beamwidth	100°
Front-to-Back Ratio (dB)	8
Axial Ratio - Typical (dB)	2.0

MECHANICAL SPECIFICATIONS

Dimensions - length x width x height - mm (inches)	132.1 x 132.1 x 17.8 (5.2 x 5.2 x .71)
Weight - kg (lbs.)	0.37 (0.8)
Mounting Style	Threaded Stud 2x #10-32
Radome Material	White High Strength PC
Lightning Protection	DC Grounded
Connector Type	Type N-Female, RP-TNC Female, RP-SMA-Female, SMA-Female


ENVIRONMENTAL SPECIFICATIONS

Operating Temperature - °C (°F)	-30 to +70°C (-22 to +158°F)
Storage Temperature - °C (°F)	-40 to +85°C (-40 to +185°F)
Impact Resistance	1 lb. ball drop, 24"
Salt	MIL-STD-810
Vibration	MIL-STD-810
Shock	IEC 68-2-27
Humidity	IEC 68-2-27
Ingress Protection Rating	IP67

CONFIGURATION

PART NUMBER	POLARIZATION	CONNECTOR
S9025PLNF	LHCP	N Female
S9025PLRASMAF	LHCP	Right Angle, SMA Female
S9025PLRTN	LHCP	RP TNC
S9025PLSMF	LHCP	SMA Female
S9025PRNF	RHCP	N Female
S9025PRRASMAF	RHCP	Right Angle, SMA Female
S9025PRRTN	RHCP	RP TNC
S9025PRSMF	RHCP	SMA Female

RADIATION PATTERNS



TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

05/25 Original