

2.4/5 GHz 2.5/4 dBi Wi-Fi Mini MIMO Omni Antenna with 6 RPSMA Male Connectors

The 2.4/5 GHz ceiling mount multiple-input and multiple-output (MIMO) omnidirectional antenna is designed to be operated with any manufacturer's enterprise-class 802.11n MIMO access points (APs). The antenna features six integrated 2.4 and 5 GHz dual-band omni antennas in one enclosure, making it an ideal and aesthetically-pleasing antenna to support demanding applications in next generation IEEE 802.11n indoor wireless communication systems.

Every Ventev antenna is RoHS compliant and covered by Ventev's two-year TerraNet warranty program.

For more information or to purchase, contact Ventev: 800.851.4965 or sales@ventev.com.




SPECIFICATIONS


SKU	375087
Model Number	M6025040MO1D3620P
Frequency Range	2.4/5 GHz
Gain	2.5/4 GHz
Vertical Beamwidth	55° / 60°
Horizontal Beamwidth	360°
Polarization	Vertical
Bandwidth	83/700 MHz
VSWR	≤ 2.0 / ≤ 2.5
Maximum Input Power	50 W
Nonimal Impedance	50 Ohm
Number of Ports/Cable	6 x 36" Plenum
Connector Type	RPSMA Male
Dimensions	7.0 x 5.0 x 1.9"
Weight	0.68 lb
Mounting Style	Ceiling Mount
Operating Temperature	-40°F to 158°F

Radiation Patterns

2.4 GHz




E Plane




H Plane

5 GHz



E Plane



H Plane

Terrawave by Ventev

2.4/5 GHz 2.5/4 dBi Wi-Fi Mini MIMO Omni Antenna with 6 RPSMA Male Connectors

Mounting Information

