



[Installation video](#)



[Installation instructions](#)



Contact technical support:

1-888-201-6073

[techsupport@jmawireless.com](mailto:techsupport@jmawireless.com)

General	Specification	
<b>Interface/gender</b>	N male	
<b>Cables supported<sup>1</sup></b>	Andrew FSJ4, FSJ4RK, FSJ4RN-50; RFS SCF 12; NK Draka RFF 1200; Eupen EC4HF; Leoni Flexline 1/2" S; LS/Superior Essex HFSC 12D; Hansen RF5012S, RF5012SZ; Rosenbeger SL 1/2" S; HUBER+SUHNER SF 1/2 HF	
<b>Weight</b>	125.6 g   0.277 lb	
<b>JMA Weather Protection System</b>	WPS-N-4S	
Tools required	JMA part number	Comment
<b>Cable preparation</b>	SP-12S	No coring required
<b>Connector compression</b>	HCG-FRAMESET-1/2, HCG-CC	Insert B
<b>Torque wrench</b>	TW1412	14 lbf·in   1.58 N·m
Frequency band	VSWR	Return loss (dB)
<b>555–1000 MHz (0-1 GHz)</b>	1.02	40
<b>1000–2700 MHz (1-2 GHz)</b>	1.03	38
<b>2700–3800 MHz (2-4 GHz)</b>	1.05	30
<b>3800–6000 MHz (4-6 GHz)</b>	1.08	26
Electrical	Specification	Comment
<b>Connector impedance</b>	50 ohm	
<b>Operating frequency band</b>	DC–6 GHz	
<b>3rd order IMD dynamic, (PIM)</b>	-161 dBc, typical	IEC 60237-02
<b>DC test voltage</b>	2000 V	
<b>Center contact resistance</b>	≤ 1.5 milliohm	
<b>Outer contact continuity</b>	0.3 milliohm max.	
<b>Average power</b>	600 W @ 900 MHz	
<b>Peak power, max.</b>	10 kW	
<b>Insertion loss, typical</b>	0.05 dB	Per connector
<b>Shielding effectiveness</b>	< -120 dB	@ 0-1 GHz
Mechanical	Specification	Comment
<b>Pull force combined</b>	.78 kN   >175 lb	Cable limited
<b>Cable retention torque</b>	6.7 N·m   5 lbf·ft	Cable limited
<b>Interface durability</b>	500 cycles	IEC 61169-4:9.5
Environmental	Specification	Test
<b>Operating temperature</b>	-55 °C to +85 °C (-67 °F to 185 °F)	
<b>Storage temperature</b>	-55 °C to +85 °C (-67 °F to 185 °F)	
<b>Accelerated UV</b>	1000 hr	ASTM G154
<b>Immersion test method</b>	Mated & unmated, IP68	IEC 60529:2001 & ANSI/SCTE 60
<b>Water jetting test method</b>	Mated & unmated, IP66	IEC 60529:2001
<b>Mechanical shock test method</b>	Pass	IEC 60068-2-27
<b>Thermal shock test method</b>	Pass	IEC 60068-2-14
<b>Vibration test method</b>	100 m/s <sup>2</sup> , 2 Hz to 200 Hz	IEC 61169-1:2003
<b>Corrosion test method</b>	1000 hr	IEC 60068-2-11

<sup>1</sup>For cable types not listed, please contact JMA Technical Support.

02/07/20