## **HellermannTyton**

## **Specification Sheet**

Part Number: TSR3W-6A



One Piece Surface Raceway, 1-3/4", 6.0 ft Long, PVC, White, 120ft/Carton

Article Number 250-03602

Type TSR3-6A

Color White (WH)

**Features & Benefits** 

• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance. • PVC construction is lightweight, durable and more affordable than metallic raceway systems. • Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing. • Foam tape backing with rubber based adhesive conforms to any flat surface to assist with temporary positioning and mounting. • Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor. • Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.

Quantity Per carton

_			_	_			
ם	rn	a	Inct	Des	2 C F I	nt	ınn
	ıv	u	uCL	DE	3 G I I	IJι	IUII

HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations.

**Short Description** 

One Piece Surface Raceway, 1-3/4", 6.0 ft Long, PVC, White,

120ft/Carton

**Global Part Name** 

TSR3-6A-PVC-WH

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

1.75

Width W (Metric)

44.45

Height H (Imperial)

1.0

**Height H (Metric)** 

25.40

Material

Polyvinylchloride (PVC)

**Material Shortcut** 

PVC

Flammability UL 94 V0

Halogen free No

Operating Temperature (Metric) +122°F (+50°C)

Reach Complaint(Article 33) No

ROHS Complaint Yes

Package Quantity(Imperial) 120

Package Quantity (Metric) 36.58

Customs Number 3925900000

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions