



Mesh Series

Omni Antennas ODxxM

2.4-5.85 GHz VERTICALLY POLARIZED OMNIDIRECTIONAL ANTENNA

The Mesh Series omnidirectional antenna series are designed with mesh networking in mind. With their waterproof N male connector they can be easily mounted to an enclosure like the die-cast enclosure (DCE-7x6x2) to give total wireless coverage. Various gains and frequencies are available. They are constructed of UV resistant materials and are waterproof for a long service life.

FEATURES

- Mesh networking vertically polarized omni-directionals
- Various gains available: 5dBi to 12dBi
- Various frequencies available: 2.4GHz & 5GHz
- Type N male integrated connector
- Rugged, lightweight, and waterproof


MARKETS

- Mesh networking applications
- 2 to 6 GHz wireless applications
- Point to multi-point systems
- Base station antennas
- Wi-Fi access points
- WiMax base stations


PARAMETER	
VSWR	1.5:1
Impedance	50 ohm
Input power	10W
Rate wind velocity	125 mph (56 m/sec)
Operating temperature	-40 - +70°C
IP Rating	IP53

MODEL	FREQ. (MHz)	GAIN	VERT BW	WEIGHT	DIM (L X DIA)
OD24M-5	2400-2485	5dBi	25°	0.5 lbs (0.2 kg)	12 x 0.6 in (355 x 15 mm)
OD24M-9	2400-2485	9dBi	14°	0.8 lbs (0.4 kg)	27 x 0.6 in (690 x 15 mm)
OD58M-12	5400-5850	12dBi	7°	0.65 lbs (0.5 kg)	27.5 x 0.6 in (700 x 15 mm)


ANTENNA PATTERNS



OD24M-5 E-Plane



OD24M-9 E-Plane



OD58M-12

SYSTEM ORDERING

OD _ _ M- _ _

Frequency

24 = 2400 to 2485 MHz
 35 = 3400 to 3600 MHz
 49 = 4940 to 4990 MHz
 58 = 5400 to 5858 MHz
 5W = 5150 to 5850 MHz

Gain

5 = 5dBi
 12 = 12dBi

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

06/25 Original

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015