# 1316MCLICK



Miniature Click-on Hanger for 13–16 mm cable - Hardware Sold Separately

#### **Product Classification**

Product Type Hanger kit

Ordering Note CommScope® standard product in Europe, the Middle East, and

Africa | CommScope® standard product in the United States and Canada

General Specifications

Cables per Hanger 2

**Color** Black

Hanger TypeClick-on hangerMountingM8 through hole

Dimensions

**Height** 38.1 mm | 1.5 in

Maximum Stack Height 3

 Width
 24.892 mm | 0.98 in

 Length
 55.118 mm | 2.17 in

 Compatible Diameter, maximum
 16.256 mm | 0.64 in

 Compatible Diameter, minimum
 13.716 mm | 0.54 in

Nominal Size 1/2 in | 3/8 in

**Electrical Specifications** 

Return Loss Effect 0.1 dB

DTF Effect 0.1 dB

Material Specifications

Material Type Engineered plastic

COMMSCOPE®

# 1316MCLICK

## Mechanical Specifications

**Vibration Survival** ≥4 hours at resonant frequency

#### **Environmental Specifications**

**Operating Temperature**  $-40 \,^{\circ}\text{C}$  to  $+85 \,^{\circ}\text{C}$  ( $-40 \,^{\circ}\text{F}$  to  $+185 \,^{\circ}\text{F}$ )

**Environmental Strength Capability**Double cable weight

**UV Resistance, minimum with no degradation** ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

 Height, packed
 44.7 cm | 17.598 in

 Width, packed
 39.4 cm | 15.512 in

 Length, packed
 17.7 cm | 6.969 in

Packaging quantity 10

**Weight, gross** 0.05 kg | 0.11 lb

## Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



### \* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

