

42396A-1



Butterfly Hanger for 1-1/4 in coaxial cable and elliptical waveguide 64

Product Classification

Product Type	Hanger kit
Ordering Note	CommScope® standard product in the United States and Canada

General Specifications

Cables per Hanger	1
Color	Silver
Hanger Type	Standard butterfly hanger
Mounting	3/8 in (M10) drilled cable ladder

Dimensions

Height	58.928 mm 2.32 in
Width	38.1 mm 1.5 in
Length	76.2 mm 3 in
Compatible Diameter, maximum	43.18 mm 1.7 in
Compatible Diameter, minimum	37.592 mm 1.48 in
Nominal Size	1-1/4 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Stainless steel
----------------------	-----------------

Mechanical Specifications

Vibration Survival	≥4 hours at resonant frequency
---------------------------	--------------------------------

42396A-1

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Environmental Strength Capability	Double cable weight

Packaging and Weights

Height, packed	26 cm 10.236 in
Width, packed	9 cm 3.543 in
Length, packed	9 cm 3.543 in
Packaging quantity	10
Weight, gross	0.53 kg 1.168 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

