

Lace-up Hoisting Grip for 4 in coaxial cable and elliptical waveguide
17 and 20



Product Classification

Product Type	Hoisting grip
Ordering Note	CommScope® non-standard product

General Specifications

Attachment Spacing Intervals	60.96 m 200 ft
Cable Type	Corrugated Elliptical waveguide
Hoisting Grip Type	Lace-up hoisting grip
Support Clamp	Not included
Tool Type	Hoisting grip

Dimensions

Grip Length, minimum	965.2 mm 38 in
Leader Length, minimum	508 mm 20 in
Nominal Size	4 in
Waveguide Size	WR430 WG8 R22

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Tin-coated bronze
----------------------	-------------------

Mechanical Specifications

Pull Load Capacity	226.796 kg 500 lb
---------------------------	---------------------

34759

Packaging and Weights

Packaging quantity 1
Weight, gross 1.56 kg | 3.439 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

