

Cold shrink Kit for 1/2 in through 7/8 in antenna and device 7/16 DIN connections

### **Product Classification**

**Product Type** Cold shrink kit

Ordering Note CommScope® non-standard product

General Specifications

**Application** Provides additional moisture seal for cable connections

**Applications per Kit** One 1/2 in–7/8 in

**Cable Family** AL5-50 | AVA5-50 | FSJ4-50B | FSJ4-75A | LDF4-50A | LDF4-

75 | LDF5-50A | LDF5-75 | VXL5-50

**Color** Black

**Dimensions** 

**Length** 202.946 mm | 7.99 in

Cable Diameter for Seal, maximum 21.34 mm | 0.84 in

Cable Diameter for Seal, minimum 16 mm | 0.63 in

**Inner Diameter** 53.09 mm | 2.09 in

Nominal Size 1/2 in | 7/8 in

Material Specifications

Material Type EPDM rubber

## **Environmental Specifications**

**UV Resistance Test Method**UV condensation reference ASTM-G-53, light source UVA 340 fluorescent lamp

**UV Resistance, minimum with no degradation** ≥1000 hours

Weather Resistance Test Method 04AS00-03.6.0 | MIL-STD-1344A, Method 1002

COMMSCOPE®

# 245174

# Packaging and Weights

 Height, packed
 254 mm | 10 in

 Width, packed
 63.5 mm | 2.5 in

 Length, packed
 63.5 mm | 2.5 in

Included One EPDM rubber tube | One sealing foam strip

Packaging quantity 1

**Weight, gross** 0.16 kg | 0.353 lb

### Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant





