



SnapStak® Hanger for 1-1/4 in coaxial cable

Product Classification

Product Type	Hanger kit
Product Brand	SnapStak®
Ordering Note	CommScope® standard product in Asia Pacific CommScope® standard product in Mexico, Central America, and South America CommScope® standard product in the United States and Canada

General Specifications

Cables per Hanger	1
Color	Silver
Hanger Type	Snap-in hanger
Mounting	3/4 in drilled cable ladder

Dimensions

Height	40.894 mm 1.61 in
Maximum Stack Height	2
Width	40.132 mm 1.58 in
Length	81.026 mm 3.19 in
Compatible Diameter, maximum	43.18 mm 1.7 in
Compatible Diameter, minimum	37.592 mm 1.48 in
Nominal Size	1-1/4 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

SSH-114

Material Specifications

Material Type Stainless steel

Mechanical Specifications

Vibration Survival ≥ 4 hours at resonant frequency

Environmental Specifications

Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F)

Corrosion Resistance, minimum with no degradation ≥ 500 hours in salt spray chamber

Environmental Strength Capability Double cable weight

Packaging and Weights

Height, packed 22 cm | 8.661 in

Width, packed 14.6 cm | 5.748 in

Length, packed 14.8 cm | 5.827 in

Packaging quantity 10

Weight, gross 0.52 kg | 1.146 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power