ClearLink® | Multiband Directional Antenna

Indoor/Outdoor



General Information

Westell's multiband directional antenna is designed to operate in multiple bands of frequencies while focusing energy in a particular direction. Westell's multiband directional antenna is quality designed with weather resistant radome enclosure.

Product Highlights

- Panel Design
- · Weather Resistant Radome
- IP56

Frequency Range

- 698-960 MHz
- 1710-2700 MHz

Electrical Specifications

Horizontal Beamwidth	See Radiation Patterns Below
Vertical Beamwidth	See Radiation Patterns Below
Gain, dBi (Typ) 698-960 MHz 1710-2700 MHz	7 7
Polarization	Vertical, Linear
Impedance	50 Ohm
VSWR	
698-806 MHz	≤ 1.6:1
806-960, 1710-2700 MHz	≤ 1.5:1
PIM	≤-153 dBc (2 tone x 43 dBm)
Front to Back Ratio, dB (Typ) 700 MHz 850 MHz 1900 MHz 2100 MHz 2300 MHz Maximum Input Power	13 8 19 15 22 50 Watts Max -
,	2W typical application
Lightning Protection	Direct Ground

Specifications subject to change without notice.



Ordering information

Part Number	Descriptions
CS03-012-389	ClearLink-D/698-2.7K/N
CS03-012-389-02	ClearLink-D/698-2.7K/4310

Mechanical Specifications

Prechamical opecinications	
Case Material	ABS with UV Protection
Operating Temperature Range	-40° C to +70° C
Dimensions	8.19 x 7.00 x 1.72 in.
Weight	1 lb.
Pigtail	Low PIM plenum rated 11 in. cable
Connectors	N-Female, and 4.3-10 Female
Universal bracket included for additional mounting options (U-bolt compatible)	



ClearLink® | Multiband Directional Antenna

Indoor/Outdoor




Radiation Patterns


704 MHz





824 MHz







Vertical, 59° Beamwidth

Horizontal, 115° Beamwidth


1990 MHz








2100 MHz





2350 MHz



