

ANT220K WIDEBAND DISCONE ANTENNA


The Telewave ANT220K is an extremely rugged, wideband discone antenna for all frequencies between 30 MHz and 3 GHz. The wide vertical beamwidth of discone antennas allows clear communication for ground and ground-to-air applications.

Telewave discone antennas are designed to survive the most extreme conditions, where conventional antennas often fail. They are field-proven in US and overseas deployments and support many voice and data requirements in multiple bands.

Each discone is constructed from Mil. Spec. 6061-T6 solid aluminum, fully welded at all joints for maximum strength. All internal junctions are enclosed within a ruggedized radome to ensure survivability in the worst environments.

The radome and Txytan™ coating on all metal surfaces ensures complete protection from corrosive gases, ultraviolet radiation, salt spray, acid rain and sand storms in desert environments.


The ANT220K is designed to be clamped to a 1.5"-3.5" diameter galvanized steel support pipe. An ANTC482 dual clamp set is included.




ANTC482



SPECIFICATIONS (PRELIMINARY)	
Frequency (continuous)	30 MHz - 3000 MHz
Power rating (typ.)	500 watts
Gain (typ.)	0 dBd
Impedance	50 ohms
VSWR	2.5:1 or less
Pattern	Omnidirectional
Termination	N-Male or 7-16 DIN on RG-393 feed cable
Vertical beamwidth (nom.)	110 degrees (varies with frequency)
Wind rating / 0.5" ice	150 / 125 MPH
Maximum exposed area	2.25 ft. ²
Lateral thrust at 100 MPH	90 lb
Bending moment at 100 MPH	180 ft. lb (top clamp, flat plate equiv.)
Dimensions	58" H x 38" W (at skirt base)
Weight (antenna + clamps)	61 lb
Shipping weight	110 lb



E-plane: 100 MHz



E-plane: 400 MHz