



TF-M3S2-20

Tower Face Mount with dual 20 ft x 3-1/2 in OD face pipe supports, includes pipe

Dimensions

Face Width	508.0 mm		20.0 in
Pipe Outer Diameter	114.3 mm		4 1/2 in
Face Support Pipe Diameter	88.9 mm		3.5 in
Height	1600.2 mm		63.0 in
Length	304.8 mm		12.0 in
Mounting Diameter, maximum	203.2 mm		8 in
Mounting Diameter, minimum	0.0 mm		0 in
Weight	313.5 kg		691.1 lb
Width	6096.0 mm		240.0 in

Environmental Specifications

Wind Rating	120 mph (BWS) at 100 ft AGL
Wind Rating Test Method	TIA/EIA-222

General Specifications

Product Type	Tower face mount
Pipe Length	1600.2 mm 63.0 in
Pipe, quantity	1
Tower Taper	Non-tapered Tapered
Includes	Crossover plates Pipes Saddle mounts
Material Type	Hot dip galvanized steel
Mounting	Angle 60°, 203.2 mm (8 in) Angle 90°, 152.4 mm (6 in) Straight or tapered legs up to 203.2 mm (8 in) OD
Package Quantity	1

* Footnotes

Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code
-------------	--