# Product Specifications





Uniprise Solutions
760087718 | RFE-MOD-024-5K-MPO-LC02-KYL
ReadyPATCH® LazrSPEED® Keyed Module, 24 LC ports, yellow

#### **Construction Materials**

Fiber Type LazrSPEED® 550, 50 µm multimode fiber (OM4)

Total Fibers, quantity 24

#### **Dimensions**

 Depth
 127.00 mm | 5.00 in

 Height
 27.94 mm | 1.10 in

 Width
 129.54 mm | 5.10 in

## **Environmental Specifications**

Safety Standard UL

### **General Specifications**

Interface, front LC

Total Ports, quantity, front 24

Interface Feature, front Keyed

Color, front Yellow

Adapters, quantity, front 12

Brand ReadyPATCH®

Shuttered Yes
Interface, rear MPO Male
Adapters, quantity, rear 2

Interface Feature, rear Standard
Color, rear Gray
Package Quantity 1

# **Optical Performance**

Insertion Loss Change, mating 0.30 dB
Insertion Loss Change, temperature 0.30 dB
Insertion Loss, maximum 0.90 dB
Return Loss, minimum 20.0 dB

# **Regulatory Compliance/Certifications**

**Agency**RoHS 2011/65/EU

Compliant

ISO 9001:2008 Designed, manufactured and/or distributed under this quality management system

# **Product Specifications**



760087718 | RFE-MOD-024-5K-MPO-LC02-KYL



#### **Included Products**

460117427 (Product Component—not orderable) — LC Duplex Hybrid Keyed Adapter, Yellow

#### \* Footnotes

Insertion Loss Change, mating Maximum insertion loss change after 500 matings

Insertion Loss Change, temperature Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)

# Product Specifications



#### 460117427

#### LC Duplex Hybrid Keyed Adapter, Yellow

#### **Construction Materials**

Fiber Type LazrSPEED® 150, 50 µm multimode fiber (OM2+) | LazrSPEED® 300, 50 µm multimode fiber

(OM3) | LazrSPEED® 550, 50 μm multimode fiber (OM4) | OptiSPEED®, 62.5 μm multimode fiber (OM1) | TeraSPEED®, zero water peak singlemode fiber (G.652.D, G.657.A1 or G.652.D,

G.657.A1 | OS2)

Alignment Sleeve Material Zirconia

## **General Specifications**

LC Interface Body Style Duplex Interface Feature Keyed Color Yellow Mount Type No flange

Package Quantity

**Product Type** Adapter Shuttered No Total Ports, quantity

TIA/EIA-568-B.3 | TIA/EIA-604 FOCIS-3 Transmission Standards

# **Regulatory Compliance/Certifications**

**Agency** Classification RoHS 2011/65/EU Compliant

ISO 9001:2008 Designed, manufactured and/or distributed under this quality management system

