


POWERED BY



## MC-K6M-B

**Monopole Co-location T-Frame kit, 12 in to 50 in OD, 6 ft 6 in face**

### Dimensions

Face Width	2.0 m   6.5 ft
Mounting Diameter, maximum	1270.0 mm   50 in
Mounting Diameter, minimum	304.8 mm   12 in
Height	254.0 mm   10.0 in
Length	914.4 mm   36.0 in
Mounting Circumference, maximum	3990.3 mm   157.1 in
Mounting Circumference, minimum	1196.3 mm   47.1 in
Weight	281.2 kg   619.9 lb
Width	1981.2 mm   78.0 in

### Environmental Specifications

Man Rating	250 lb vertical man load at 15 mph (BWS)
Wind Rating	120 mph (BWS) at 150 ft AGL   140 mph (3-second gust) at 150 ft AGL using Exposure D per FBC
Wind Rating Criteria	Four 72 in x 8 in panel antennas per sector
Wind Rating Test Method	TIA/EIA-222-G

### General Specifications

Product Type	Co-location t-frame kit
Pipe, quantity	0
Includes	Cellular pipe frames   Pipe mounts   Ring mount   Stand-off arms
Material Type	Hot dip galvanized steel
Mounting	Monopole, 304.8–1270 mm (12–50 in) OD
Package Quantity	1
Sectors, quantity	3
Stand-off Distance	914.4 mm   36.0 in

### Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

#### \* Footnotes

Man Rating	BWS—Base Wind Speed
Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code