



[Installation video](#)



[Installation instructions](#)



Contact technical support:

1-888-201-6073

techsupport@jmawireless.com

| General | | Specification |
|-------------------------------|---------------------------------------|-------------------------------|
| Interface/gender | N Female | |
| Cables supported ¹ | Andrew HJ5, HJ5RP, HJ5RPV; RFS HCA78 | |
| Weight | 247.2 g 0.545 lb | |
| JMA Weather Protection System | N/A | |
| Tools required | | JMA part number |
| Cable preparation | SP-78PL | Comment |
| Connector compression | HCG-FRAMESET-7/8, HCG-CC | No coring required |
| Hex width | 35 mm 1-3/8 in. | |
| Frequency band | | VSWR |
| 555–1000 MHz | 1.02 | Return loss (dB) |
| 1000–2700 MHz | 1.03 | 40 |
| 2700–3800 MHz | 1.05 | 36 |
| 3800–6000 MHz | 1.08 | 32 |
| | | 28 |
| Electrical | | Specification |
| Connector impedance | 50 ohm | Comment |
| Operating frequency band | DC–5 GHz | |
| 3rd order IMD dynamic, (PIM) | -161 dBc, typical | IEC 60237-02 |
| DC test voltage | 4000 V | |
| Center contact resistance | ≤0.4 milliohm | |
| Outer contact continuity | 1.5 milliohm max. | |
| Average power | 3000 W @ 900 MHz | |
| Peak power, max. | 40 kW | |
| Insertion loss, typical | 0.05 dB | Per connector |
| Shielding effectiveness | < -120 dB | @ 0-1 GHz |
| Mechanical | | Specification |
| Pull force combined | 1.56 kN > 350 lb | Comment |
| Cable retention torque | 21.69 N·m 16 lbf·ft | Cable limited |
| Interface durability | 50 cycles | Cable limited |
| | | IEC 61169-4:9.5 |
| Environmental | | Specification |
| Operating temperature | -55 °C to +85 °C (-67 °F to 185 °F) | Test |
| Storage temperature | -55 °C to +85 °C (-67 °F to 185 °F) | |
| Accelerated UV | 1000 hr | ASTM G154 |
| Immersion test method | Mated & unmated, IP68 | IEC 60529:2001 & ANSI/SCTE 60 |
| Water jetting test method | Mated & unmated, IP66 | IEC 60529:2001 |
| Mechanical shock test method | Pass | IEC 60068-2-27 |
| Thermal shock test method | Pass | IEC 60068-2-14 |
| Vibration test method | 100 m/s ² , 2 Hz to 200 Hz | IEC 61169-1:2003 |
| Corrosion test method | 1000 hr | IEC 60068-2-11 |

¹For cable types not listed, please contact JMA Technical Support.