



FPX-5FRA08-2880 | 320000113910

FPX Fiber Termination/Splice Panel, 288 LC/UPC, singlemode, 5RU, 19 in, putty white

Body Features

| | |
|---------------|---------------|
| Cable Entry | Front |
| Cable Exit | Front |
| Chassis Color | Putty white |
| Finish | Powder coated |

Configuration Features

| | |
|-----------------------------|---------------|
| Access | Rear |
| Number of Ports | 288 |
| Front Connector Type | LC/UPC |
| Configuration | Adapters only |
| Rear/Far End Connector Type | LC/UPC |

Dimensions

| | |
|--------|------------------------|
| Depth | 304.800 mm 12.000 in |
| Height | 222.250 mm 8.750 in |
| Width | 482.600 mm 19.000 in |

Other

| | |
|-----------------------|---------|
| Adapter Pack Capacity | 12 Pack |
|-----------------------|---------|

Packaging Features

| | |
|--------------------|--|
| Includes | Installation Instruction Mounting hardware |
| Packaging Method | Box/Carton |
| Packaging Quantity | 1 |

Product Availability

| | |
|--------|-------------------------------|
| Region | Latin America North America |
|--------|-------------------------------|

Product Type Features

| | |
|--------------|--------------------------------|
| Product Type | Fiber Termination/Splice Panel |
| System | FPX |
| Rack Units | 5.0 |
| Optical Mode | Singlemode |

Usage Conditions

FPX-5FRA08-2880 | 320000113910

Storage Temperature -40 – 185 °F | -40 – 85 °C

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant