

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Protect It! 7-Outlet Surge Protector, 25 ft. Cord, 2160 Joules, Black Housing

MODEL NUMBER: SUPER725B











Safeguard your workstation or home electronics against surges, spikes and line noise. Ideal for protecting your computer, printer, scanner, external hard drive and other sensitive electronics.

Description

Perfect for your home or office workstation, the SUPER725B Protect It! 7-Outlet Surge Protector features a surge suppression rating of 2160 joules to defend your sensitive electronic components against strong surges and spikes. In fact, Tripp Lite will repair or replace any connected equipment damaged by surges, including direct lightning strikes, up to \$75,000 for life (valid in the U.S., Canada and Puerto Rico only).

The SUPER725B includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression, as well as technology that filters out disruptive EMI/RFI line noise, preventing interference from disrupting your electronics and inflicting damage or data loss.

Your computer and peripherals plug into seven NEMA 5-15R outlets. Two outlets are mounted on the side to let the SUPER725B accommodate three bulky transformers without blocking adjacent outlets. Integrated 15-amp circuit breaker protects all outlets against dangerous overloads. On/off switch provides one-touch control over connected equipment. A green LED indicates protection status, while a red LED assures that your wall outlet is properly grounded.

The 25-foot AC power cord allows the SUPER725B to reach distant outlets, while its right-angle NEMA 5-15P plug allows equipment and furniture to be moved flush against the wall to save space. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

Features

2160-Joule Surge Protection for Home or Office Electronics2160-joule rating protects your computer, printer, scanner, external hard drive and other sensitive electronic components against even the strongest surges and spikesBacked by Tripp Lite's \$75,000 Ultimate Lifetime Insurance for any connected components damaged by power surge (U.S., Canada and Puerto Rico only)Full normal mode (H-N) and

Highlights

- 7 NEMA 5-15R outlets, including 3 for bulky transformers
- Surge suppression rating of 2160 joules
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker prevents dangerous overloads
- 25 ft. AC power cord with rightangle NEMA 5-15P plug

Package Includes

- SUPER725B Protect It! 7-Outlet Surge Protector, 25 ft. Cord, Black Housing
- · Owner's manual



common mode (N-G/H-G) line surge suppressionFilters out disruptive EMI/RFI line noise that can cause equipment damage or data lossExceeds IEEE 587 Category A and B surge suppression specifications 7 Outlets Accept Wide Range of Electronic Devices7 NEMA 5-15R AC outlets accept most computers and peripheralsUnique side-outlet design accommodates 3 bulky transformers without blocking other outlets

Premium Safety FeaturesAutomatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is requiredLEDs show grounding and protection status at a glance

Fits Effortlessly Into Your Workstation25 ft. AC power cord long enough to reach distant outletsSpace-saving right-angle NEMA 5-15P plug allows furniture and equipment to move flush against the wallKeyhole slots on bottom panel provide convenient wall or desk mounting optionsBlack plastic housing designed for long life

Specifications

OVERVIEW		
UPC Code	037332189844	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	144000	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	25	
Right-Angle Plug	Yes	
Input Cord Length (m)	7.62	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(7) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(4) Yes	
Outlet Orientation	Single row of 5, plus 2 side mounted outlets	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	





Switches	Two position on/off power switch	
Diagnostic LED Details	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	2160	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping Voltage (RMS)	150	
UL1449 Let Through Rating	330 L-G, 400 L-N, 400 N-G	
EMI / RFI Filtering	Up to 20 dB	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Antimicrobial Coating	No	
Color	Black	
Color (AC Line Cord)	Black	
Housing Color	Black	
Integrated Keyhole Mounting Slots	Yes	
Keyhole Slot Mounting Measurement (Center to Center)	Distance Between Slots = 78mm; Distance Between Slot Height = 24mm	
Material of Construction	Plastic	
Outlets Measurement (Center to Center)	Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm	
Receptacle Color	Black	
Shipping Dimensions (hwd / cm)	31.50 x 21.01 x 4.50	
Shipping Dimensions (hwd / in.)	12.40 x 8.27 x 1.77	
Shipping Weight (kg)	1.54	
Shipping Weight (lbs.)	3.40	
Unit Dimensions (hwd / cm)	3.91 x 6.91 x 26.16	
Unit Dimensions (hwd / in.)	1.54 x 2.72 x 10.30	
Unit Weight (kg)	1.31	
Unit Weight (lbs.)	2.89	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

SPECIAL FEATURES		
Rotatable Outlets	No	
STANDARDS & COMPLIANCE		
Canada	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
UL1449 3rd Edition (AC Suppression)	UL1449 3RD EDITION	
UL1363 (Power Tap)	UL1363	
WADDANTY		
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$75,000 Ultimate Lifetime Insurance	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies