
Cable Runway Bonding Strap Kit

Cable Runway Bonding Strap Kits provide a bonding pathway between cable runway lengths when fastened together across splices. Installation requires drilling 5/16" (127 mm) holes. Bonding Straps consist of an 8"L (200 mm) #6 AWG green insulated stranded copper conductor with horizontal yellow stripe attached at both ends to two-hole compression lugs with 1/4" (6.4 mm) bolt holes spaced on 5/8" (15.9 mm) centers.

- Overall length of 11" (280 mm)
- Available individually or in packs of 25
- Constructed of UL® Listed components, File E236184, Category KDER (US), KDER7 (Canada) - Bonding and Grounding Equipment
- Other configurations available on request

Kit consists of:

- (4) stainless steel cap screws, #1/4-20 x 3/4"L (19 mm)
- (4) flat washers, 1/4" (6.4 mm)
- (4) lock washers, 1/4" (6.4 mm)
- (4) nuts, 1/4" (6.4 mm)



ORDERING INFORMATION

Part Number	Description	Shipping Weight Ib (kg)
40164-001	#6 AWG Bonding Strap, Each	1 (0.5)
40164-025	#6 AWG Bonding Straps, Pack of 25	12 (5.0)

Toronto, Ontario, Canada +905-850-7770

Europe Buckinghamshire, UK +441628524834

Middle East & Africa Dubai, UAE +971-4-2602125

Doha, Qatar +974-4-267422 Latin America +52-55-5203-7525 Toll Free within Mexico 800-201-7592 chatsworth.com.co Asia Pacific +86 21 6880-0266 chatsworth.com.cn

