DB436-C



1-port sector (yagi) antenna, 450–470 MHz, 60° HPBW, fixed electrical tilt

- Highly directional coverage and good front-to-back ratio
- Rugged, reliable design
- Stacked arrays

General Specifications

Antenna Type Sector

Band Single band

Color Silver

Grounding Type RF connector inner conductor and body grounded to reflector and mounting bracket

Performance Note Outdoor usage

Radiator Material Aluminum

RF Connector Interface N Male
RF Connector Location Bottom

RF Connector Quantity, low band

RF Connector Quantity, total

Dimensions

 Width
 368.3 mm | 14.5 in

 Length
 889 mm | 35 in

 Depth
 25.4 mm | 1 in

Electrical Specifications

Impedance 50 ohm

Operating Frequency Band 450 – 470 MHz

Polarization Vertical

Electrical Specifications

Frequency Band, MHz 450–470
Gain, dBi 12.1
Beamwidth, Horizontal, 60

Page 1 of 2



DB436-C

degrees

Beamwidth, Vertical, degrees 44

Beam Tilt, degrees 0

Front to Pack Patie at 190° 16

Front-to-Back Ratio at 180°, dB

16

VSWR | Return loss, dB Input Power per Port,

maximum, watts

1.5 | 14.0 250

Mechanical Specifications

Wind Loading at Velocity, maximum 18.0 lbf @ 100 mph | 80.1 N @ 100 mph

Wind Speed, maximum 201 km/h | 124.896 mph

Packaging and Weights

Included U-bolts

Net Weight, without mounting kit 3.2 kg | 7.055 lb

Regulatory Compliance/Certifications

Agency Classification

CE Compliant with the relevant CE product directives

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



Included Products

11653 — V-Bolt Mounting Kit for 3 in (76.2 mm) max OD round members. Set of two V-bolts clamp sets.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance

