



Y(S)8063

Directional Yagi Antennas 809-896 MHz

TE Connectivity's Silver Series Yagi antennas represent great value while featuring the same great optimized design and plated brass connector found on premium gold series models. Each Yagi is factory tuned on a network analyzer for best power match and lowest VSWR, offering the best possible performance every time. All antennas ship complete with a mounting kit that includes stainless steel hardware.

FEATURES AND BENEFITS

- All 450 MHz and higher frequency models are delivered fully assembled
- All radial elements are secured to the boom with stainless steel hardware to prevent corrosion
- Every Yagi is tuned on a network analyzer for best power match and lowest VSWR
- All antennas ship complete with a mounting kit that includes stainless steel hardware

APPLICATIONS

- Point-to-point and multi-point/ omnidirectional outdoor antenna applications used by private organizations and government agencies around the globe
- Typical applications include transportation such as railroad switching, remote locations reporting examples that include oil fields, weather conditions and, meter data transmissions for utilities

ELECTRICAL SPECIFICATION


Model Name	Y(S)8063
Operating Frequency (MHz)	809-896
VSWR	< 2:1
Return Loss - max (dB)	-10
Gain (dBd)	6.0
Front-to-Back Ratio (dBd)	15
Max Power - Ambient 25°C (W)	300
Nominal Impedance (Ohms)	50
Polarization	Vertical
Pattern	Directional
Horizontal Plane 3 dB Beamwidth	89°
Vertical Plane 3 dB Beamwidth	65°
Tuning	Fixed
Transmitting/Receiving	Both

MECHANICAL SPECIFICATION


Dimensions - L x H - cm (inches)	42.55 x 18.42 (16-3/4 x 7-1/4)
Boom Diameter - cm (inches)	2.22 (7/8)
Weight - kg (lbs.)	0.79 (1.75)
Cable Type	N/A
Connector	N-female
Color	Bright dipped aluminum
Lightning Protection	Lightning arrestor - LABH350NN (sold separately)
Mounting Kit (included)	Yagi mounting kit for 7/8-inch boom

ENVIRONMENTAL SPECIFICATION

Operating Temperature - °C (°F)	-50 to +85°C (-58 to +185°F)
Rated Wind Velocity - km/hr (mph)	241 (150)
Equivalent Flat Area - sq. km (sq. ft.)	1.42 (0.1516)



Vertical-to-Vertical Polarization Azimuthal Pattern (Y, Z, or E-plane)



Horizontal-to-Horizontal Polarization Azimuthal Pattern (Y, Z, or H-plane)

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

05/25 Original