Product Specifications



POWERED BY





PM-SC4-B

Universal Open Face Pipe Mount Kit for 4-1/2 in OD pipe



Dimensions

 Mounting Diameter, maximum
 203.2 mm
 | 8 in

 Mounting Diameter, minimum
 0.0 mm
 | 0 in

 Pipe Outer Diameter
 114.3 mm
 | 4 1/2 in

 Height
 127.0 mm
 | 5.0 in

 Length
 304.8 mm
 | 12.0 in

 Weight
 49.8 kg
 | 109.8 lb

 Width
 304.8 mm
 | 12.0 in

Environmental Specifications

Wind Rating 120 mph (BWS) at 150 ft AGL

Wind Rating Test Method TIA/EIA-222

General Specifications

Product Type Pipe mount

Pipe, quantity 0

Stand-off Distance 203.2 mm | 8.0 in

Tower Taper Non-tapered | Tapered

Includes Sliding pipe mount brackets | Universal saddle mount

Material Type Hot dip galvanized steel

Mounting Angle 60°, 203.2 mm (8 in) | Angle 90°, 152.4 mm (6 in) | Straight or tapered legs up to

203.2 mm (8 in) OD

Note One 8 ft microwave antenna with stiff arm

Package Quantity 1

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2008 Designed, manufactured and/or distributed under this quality management system

* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code