



Item #	Description	1-9	10-24	25-99	100+
--------	-------------	-----	-------	-------	------

## M12 D-Coded 4 Position Cables for Ethernet and Fieldbus Applications

L-com offers popular 22 AWG 2-pair, 4 Position, D-coded M12 cable assemblies for use in Ethernet and fieldbus applications. These robust assemblies are 100% factory tested and feature UV and chemical resistant PUR jackets. Applications for these assemblies include manufacturing, process control, factory automation and more. Contact us today with your custom M12 requirements.

## M12 4 Position D-Coded Male to Male Cable Assemblies

M12M124D-0.5	M12 4 Position D-Coded Male/Male Cable Assembly, 0.5m	13.34	13.07	12.81	CALL
M12M124D-1	M12 4 Position D-Coded Male/Male Cable Assembly, 1.0m	14.37	14.08	13.80	CALL
M12M124D-2	M12 4 Position D-Coded Male/Male Cable Assembly, 2.0m	16.43	16.10	15.77	CALL
M12M124D-3	M12 4 Position D-Coded Male/Male Cable Assembly, 3.0m	18.49	18.12	17.75	CALL
M12M124D-5	M12 4 Position D-Coded Male/Male Cable Assembly, 5.0m	20.55	20.14	19.73	CALL

## M12 4 Position D-Coded Male (Straight) to Male (Right Angle) Cable Assemblies

M12M12R4D-0.5	M12 4 Position D-Coded Male/Male Right Angle Cable Assembly, 0.5m	13.34	13.07	12.81	CALL
M12M12R4D-1	M12 4 Position D-Coded Male/Male Right Angle Cable Assembly, 1.0m	14.37	14.08	13.80	CALL
M12M12R4D-2	M12 4 Position D-Coded Male/Male Right Angle Cable Assembly, 2.0m	16.43	16.10	15.77	CALL
M12M12R4D-3	M12 4 Position D-Coded Male/Male Right Angle Cable Assembly, 3.0m	18.49	18.12	17.75	CALL
M12M12R4D-5	M12 4 Position D-Coded Male/Male Right Angle Cable Assembly, 5.0m	20.55	20.14	19.73	CALL

## M12 4 Position D-Coded Male to Female Cable Assemblies

M12M12F4D-0.5	M12 4 Position D-Coded Male/Female Cable Assembly, 0.5m	15.40	15.09	14.78	CALL
M12M12F4D-1	M12 4 Position D-Coded Male/Female Cable Assembly, 1.0m	16.43	16.10	15.77	CALL
M12M12F4D-2	M12 4 Position D-Coded Male/Female Cable Assembly, 2.0m	18.49	18.12	17.75	CALL
M12M12F4D-3	M12 4 Position D-Coded Male/Female Cable Assembly, 3.0m	20.55	20.14	19.73	CALL
M12M12F4D-5	M12 4 Position D-Coded Male/Female Cable Assembly, 5.0m	23.64	23.17	22.69	CALL

### M12 4 Position D-Coded Male to RJ45 Male Cable Assemblies

M12RJ454D-0.5	M12 4 Position D-Coded Male/RJ45 Male Cable Assembly, 0.5m	13.34	13.07	12.81	CALL
M12RJ454D-1	M12 4 Position D-Coded Male/RJ45 Male Cable Assembly, 1.0m	14.37	14.08	13.80	CALL
M12RJ454D-2	M12 4 Position D-Coded Male/RJ45 Male Cable Assembly, 2.0m	18.49	18.12	17.75	CALL
M12RJ454D-3	M12 4 Position D-Coded Male/RJ45 Male Cable Assembly, 3.0m	22.61	22.16	21.71	CALL
M12RJ454D-5	M12 4 Position D-Coded Male/RJ45 Male Cable Assembly, 5.0m	31.88	31.24	30.60	CALL

## M12 A-Coded 5 Position Cables for Sensor and Fieldbus Applications

L-com stocks A-coded 5 Position M12 cable assemblies for use in sensor and fieldbus applications. These rugged cables feature PUR jackets, 22 AWG stranded conductors and are 100% factory tested to ensure system uptime.

## M12 5 Position A-Coded Female to Cut End Cable Assemblies

M12F0E5A-1	M12 5 Position A-Coded Female/Cut End, 1.0m	10.56	9.93	9.29	CALL
M12F0E5A-2	M12 5 Position A-Coded Female/Cut End, 2.0m	13.34	12.54	11.74	CALL

## M12 5 Position A-Coded Male to Male Cable Assemblies

M12M125A-0.5	M12 5 Position A-Coded Male/Male Cable Assembly, 0.5m	14.37	14.08	13.80	CALL
M12M125A-1	M12 5 Position A-Coded Male/Male Cable Assembly, 1.0m	16.43	16.10	15.77	CALL
M12M125A-2	M12 5 Position A-Coded Male/Male Cable Assembly, 2.0m	19.52	19.13	18.74	CALL
M12M125A-3	M12 5 Position A-Coded Male/Male Cable Assembly, 3.0m	22.61	22.16	21.71	CALL
M12M125A-5	M12 5 Position A-Coded Male/Male Cable Assembly, 5.0m	27.76	27.20	26.65	CALL

## M12 5 Position A-Coded Male to Female Cable Assemblies

M12M12F5A-0.5	M12 5 Position A-Coded Male/Female Cable Assembly, 0.5m	16.43	16.10	15.77	CALL
M12M12F5A-1	M12 5 Position A-Coded Male/Female Cable Assembly, 1.0m	18.49	18.12	17.75	CALL
M12M12F5A-2	M12 5 Position A-Coded Male/Female Cable Assembly, 2.0m	21.58	21.15	20.72	CALL
M12M12F5A-3	M12 5 Position A-Coded Male/Female Cable Assembly, 3.0m	24.67	24.18	23.68	CALL
M12M12F5A-5	M12 5 Position A-Coded Male/Female Cable Assembly, 5.0m	30.85	30.23	29.62	CALL

## M12 4 Position and 5 Position Adapters

L-com stocks a multitude of M12 adapters including T style, I style and Y style M12 4 Position and 5 Position adapters. These rugged adapters are designed for use in harsh environments requiring temperature ranges from -25°C to 90°C.

### M12 A-Coded 3 Way T Style Adapters

ADPT-M124MT	M12 4 Position 3 Way Male T Adapter	17.95	17.59	17.23	CALL
ADPT-M125MT	M12 5 Position 3 Way Male T Adapter	18.95	18.57	18.19	CALL
ADPT-M124FT	M12 4 Position 3 Way Female T Adapter	20.95	20.53	20.11	CALL
ADPT-M125FT	M12 5 Position 3 Way Female T Adapter	22.95	22.49	22.03	CALL

### M12 A-Coded 2 Way I Style Adapters

ADPT-M124MI	M12 4 Position Inline Male I Adapter	10.95	10.73	10.51	CALL
ADPT-M125MI	M12 5 Position Inline Male I Adapter	11.95	11.71	11.47	CALL
ADPT-M124FI	M12 4 Position Inline Female I Adapter	13.95	13.67	13.39	CALL
ADPT-M125FI	M12 5 Position Inline Female I Adapter	14.95	14.65	14.35	CALL

### M12 A-Coded 3 Way Y Style Adapters

ADPT-M124MY	M12 4 Position 3 Way Male Y Adapter	14.95	14.65	14.35	CALL
ADPT-M125MY	M12 5 Position 3 Way Male Y Adapter	17.95	17.59	17.23	CALL
ADPT-M124FY	M12 4 Position 3 Way Female Y Adapter	18.95	18.57	18.19	CALL
ADPT-M125FY	M12 5 Position 3 Way Female Y Adapter	20.95	20.53	20.11	CALL