



CCFDFR

by Burndy
Catalog ID: CCFDFR

Prop 65 Notice

Clear Polycarbonate H-Tap-Flame Retardant Cover, 250kcmil, 600V.

- Connector end stops
- Flexible fingers
- snap tight latches
- 2piece construction
- magnifying lens

Two-Piece design with Positive Locking Latch to ensure correct installation, preventing opening after installation and eliminating the need for taping

Product Details

General

| | |
|-----------------------|--|
| Application | Flame Retardant Cover, With Positive Locking Latch to ensure correct installation, preventing opening after installation and eliminating the need for taping |
| Color | Clear |
| Color Code | Purple |
| Connector Type | H-Tap |
| Fire Resistance | Yes |
| Material | Polycarbonate |
| Operating Temperature | 90 °C |
| Plated | N |
| Plating Type | Unplated |
| Sub Brand | CRIMPIT |
| Temperature Rating | 194 |
| Type | H-Tap Connector |
| UPC | 781810438152 |
| UPC 12 Digit | 7818104381522 |

Dimensions

| | |
|---------------------------------|---------|
| Dimension - Height inch | 1.82 in |
| Dimension - L Length Overall mm | 129 mm |
| Dimension - Length Overall inch | 5.06 in |
| Dimension - Width inch | 1.48 in |

Electrical Ratings

| | |
|--------------------------|-------|
| Rating - KVA | 35 kV |
| Rating - Minimum Voltage | 600 |

| | |
|-------------------|-------|
| Voltage - Maximum | 35000 |
| Voltage Rating | 600 V |

Conductor Related

| | |
|-----------------------------------|-----------|
| Conductor - Copper Str Size | 250 kcmil |
| Conductor - Copper Str Size Range | 250 kcmil |
| Conductor - Max Length | 0.95 in |

Certifications and Compliance

| | |
|------------------------------------|-----|
| Certification - 94V0 Rated | Y |
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)