



## PM-SU4L-B

**Universal Adjustable Sliding Pipe Mount Kit for 4-1/2 in OD pipe, 6–14 in stand-off**



### Dimensions

Mounting Diameter, maximum	203.2 mm		8 in
Mounting Diameter, minimum	0.0 mm		0 in
Pipe Outer Diameter	114.3 mm		4 1/2 in
Height	127.0 mm		5.0 in
Length	304.8 mm		12.0 in
Weight	40.9 kg		90.2 lb
Width	304.8 mm		12.0 in

### Environmental Specifications

Wind Rating	120 mph (BWS) at 150 ft AGL
Wind Rating Test Method	TIA/EIA-222

### General Specifications

Product Type	Pipe mount
Pipe, quantity	0
Stand-off Distance	355.6 mm   14.0 in
Tower Taper	Non-tapered   Tapered
Includes	Sliding pipe mount brackets   Universal saddle mount
Material Type	Hot dip galvanized steel
Mounting	Angle 60°, 203.2 mm (8 in)   Angle 90°, 152.4 mm (6 in)   Straight or tapered legs up to 203.2 mm (8 in) OD
Note	One 8 ft microwave antenna with stiff arm
Package Quantity	1
Stand-off Distance, adjustable	6–14 in   15.2–35.6 cm

### Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

### \* Footnotes

Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code
-------------	--